



(Fan/Light/Heater – 80 CFM)



**4" Duct (Standard):**  
80 CFM/1.5 Sones @ 0.1 SP, 11.7 Watts



## Description

Low noise ceiling mount ventilating fan, light, and heat.  
cUL listed and Home Ventilating institute (HVI) certified.

## DC Motor/Blower

- Power rating of 120 volts/60Hz
- DC brushless motor engineered to run continuously
- Motor equipped with thermal cutoff fuse
- Removable with permanently lubricated plug-in motor
- Built-in soft start function to increase bearings' life
- Automatically powers OFF when impeller is locked abnormally

## Housing

- Galvanized steel body
- Detachable 4" diameter duct adapter
- Built-in backdraft damper
- Easy installation

## Grille

- Attractive design using PBT material
- 60W maximum lamp provides bright ceiling light (not included)

## Heater


- 1300W heating element evaluated by cUL for safety standards
- Heater module equipped with thermal cutoff fuse and thermostat

## Warranty


- 3-year limited warranty

## TYPICAL SPECIFICATION

Ventilation fan shall be Delta Breez model RAD80L; brushless DC motor engineered to run continuously for a minimum 70,000 hours; airflow rating of 80 CFM ( $\pm 10\%$ ) and 1.5 Sones at 0.1 static pressure. Power consumption approximately 11.7 Watts with an efficiency rating approximately 7.0 CFM/Watt. Duct diameter no less than 4" Built-in thermostat to regulate temperature. Metal guard to help prevent user contact with heating wire. Heater element with 1300W and conforms to cUL safety standards. Heater module equipped with thermal cutoff fuse and thermostat.



Fan Curve



Breez RAD80L	4" Duct (Standard)
Static Pressure (inches w.g.)	0.1
Air Flow (CFM)	80
Sones	1.5
Power Consumption (Watts)	11.7
Energy Efficiency (CFM/Watt)	7.0
Current (Amps)	12
Power Rating (V/Hz)	120 / 60
Heating element (Watts)	1300
Total power (Watts)	1400

Model	Quantity	Comments	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date: