



(50 CFM)



4" Duct (Standard):

50 CFM/0.7 Sones @ 0.1" SP, 5.0 Watts 38 CFM/1.3 Sones @ 0.25" SP, 7.0 Watts





Description

Low noise ceiling/wall mount ventilating Fan/LED Light rated for continuous running. Fan has been awarded ENERGY STAR® Most Efficient 2019. It is HVI, UL, and cUL certified, and can be used to comply with ASHRAE 62.2 (local and whole building continuous and intermittent operation), CA Title 24, and CALGreen requirements.

DC Motor/Blower

- Power rating of 120 volts/60Hz
- Brushless DC motor engineered to run continuously
- · Motor equipped with thermal cutoff fuse
- Removable with permanently lubricated plug-in motor
- Built-in soft start function to increase bearings' life
- Automatically powers OFF when impeller is locked abnormally
- Self-compensating motor speed for intended airflow when static pressure is encountered

Housing

- Galvanized steel body
- Detachable 4" diameter plastic duct adapter
- Built-in backdraft damper
- Easy installation

Light

- (1)13-Watt LED
- Light output 850Lumens, 3000K
- Dimmable Lighting (dimmer switch not included)
- Easy installation

Grille

- Attractive design using ABS material
- Attaches directly to housing with torsion springs


Warranty


• 3-Year limited warranty

BreezIntegrity 50F-LED				
Static Pressure (Inches w.g.)	0.1 0.25			
Air Flow (CFM)	50	38		
Sones	0.7	1.3		
Power Consumption (Watts)	50.0	7.0		
Energy Efficiency (CFM/Watts)	12.5	6.7		
Current (Amps)	0.14 Max			
Power Rating (V/Hz)	120/60			

TYPICAL SPECIFICATION

Ventilation fan shall be Delta Breez model 50F-LED; ENERGY STAR qualified with DC brushless motor engineered to run continuously for a minimum 70,000 hours; airflow rating of 50 CFM and loudness rating of 0.7 Sones at 0.1 static pressure as certified by the Home Ventilating Institute (HVI); power consumption of 5.0 Watts with efficiency rating of 12.5 CFM/Watt at 0.1" static pressure; motor lock protection and self-compensating motor speed for intended airflow when static pressure is encountered. UL and cUL listed for tub/shower enclosure when used with GFCI-protected branch circuit wiring.





, and the matter of the matter		,	
Model	Quantity	Comments	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date: