



(Fan with Humidity Sensor 50/80/110 CFM)

Full Speed:
 50 CFM / <0.3 Sones @ 0.1" SP, 4.5 Watts 80 CFM / <0.3 Sones @ 0.1" SP, 7.5 Watts 110 CFM / 0.5 Sones @ 0.1" SP, 13 Watts
 50 CFM / 0.4 Sones @ 0.25" SP, 7.5 Watts 80 CFM / 0.7 Sone @ 0.25" SP, 12.5 Watts 110 CFM / 1.0 Sones @ 0.25" SP, 19.5 Watts

HVI CERTIFIED 2100 ENERGY STAR UL US

Description

Low noise ceiling/wall mount ventilating fan rated for continuous running. Fan is ENERGY STAR qualified, HVI, UL, and cUL certified, and can be used to comply with ASHRAE 62.2 (local and whole building continuous and intermittent operation).

DC Motor/Blower

- Power Rating of 120 volts/60Hz
- Removable with permanently lubricated plug-in motor
- Full speed adjustable, 50, 80 or 110 CFM
- For humidity control mode, when humidity is above the user adjustable set-point, fan runs at full speed.
- When humidity is below the set-point, the fan runs continuously at a pre-set lower level (0, 30 or 50 CFM)
- Adjustable humidity set points between ~50% to ~80% RH
- Built-in soft start function to increase bearings' life
- Automatically powers OFF when impeller is locked abnormally

Housing

- Galvanized steel body
- Detachable 4" duct adapter
- Built-in backdraft damper
- Hanger bar included
- Easy installation with expandable extension bracket and housing flange

Grille

- Patented noise reduction design
- New appearance design enhances aesthetics
- Attractive design using ABS material
- Attaches directly to housing with torsion springs

LED Indicator



- The blue and amber LED indicator lights indicate the humidity sensor and full-speed modes are active

Warranty



- 3-Year limited warranty

TYPICAL SPECIFICATION

Ventilation fan shall be Delta Breez model ELT50-110H; ENERGY STAR qualified with Brushless DC Motor engineered to run continuously for a minimum 70,000 hours; airflow rating of 110 CFM and loudness rating of 0.5 Sones at 0.1 static pressure as certified by the Home Ventilating Institute (HVI); power consumption of 13 Watts with efficiency rating of 8.5 CFM/Watt at 0.1" static pressure; fan will feature motor lock protection and self-compensating motor speed for intended airflow when static pressure is encountered. UL and cUL listed for tub/shower enclosure when used with GFCI-protected branch circuit wiring.



Built-in Control



| BreezElite ELT50-110H | | 4" Duct Standard | | | | | | | | | | | | | |
|--|----------------------|------------------|-------|------|------|-------|------------|------|-------|------|------|-------|-----|------|-------|
| Fan Speed Static Pressure (In w.g.) | Continuous Low Speed | | | | | | Full Speed | | | | | | | | |
| | 0.1 | 0.25 | 0.375 | 0.1 | 0.25 | 0.375 | 0.1 | 0.25 | 0.375 | 0.1 | 0.25 | 0.375 | 0.1 | 0.25 | 0.375 |
| Air Flow (CFM) | 30 | 30 | 30 | 50 | 50 | 50 | 50 | 50 | 50 | 80 | 80 | 80 | 110 | 110 | 110 |
| Sones | <0.3 | <0.3 | - | <0.3 | 0.4 | - | <0.3 | 0.4 | - | <0.3 | 0.7 | - | 0.5 | 1 | - |
| Power (Watts) | 4 | 6 | 8.1 | 4.5 | 7.5 | 10.3 | 4.5 | 7.5 | 10.3 | 7.5 | 12.5 | 16.1 | 13 | 19.5 | 24.6 |
| Efficiency (CFM/Watts) | 7.5 | 5 | 3.7 | 11.1 | 6.7 | 4.9 | 11.1 | 6.7 | 4.9 | 10.7 | 6.4 | 5 | 8.5 | 5.6 | 4.5 |
| Current (Amps) | 0.45 Max | | | | | | | | | | | | | | |
| Power Rating (V/Hz) | 120 / 60 | | | | | | | | | | | | | | |

| Model | Quantity | Comments | Project: |
|-------|----------|----------|---------------|
| | | | Location: |
| | | | Architect: |
| | | | Engineer: |
| | | | Contractor: |
| | | | Submitted by: |
| | | | Date: |