



DELTA BREEZ IAQ SOLUTIONS
Perfectly Quiet. Perfectly Green.



 ENERGY STAR
AWARD 2021
PARTNER OF THE YEAR
Sustained Excellence



Performance and Exceptional Value

Delta Breez Indoor Air Quality solutions has been honored with the **2021 ENERGY STAR® Partner of the Year for Sustained Excellence** – underscoring our commitment to engineering the most innovative products for a better tomorrow.

Delta Breez is the only manufacturer to exclusively use state-of-the-art brushless DC motors in all of our fans. Here's a sampling of our rich features:

- Save more energy – up to 85% less compared to AC motors
- Exceed ENERGY STAR® efficiency requirements by more than 300%
- Long reliability and trouble-free operation, outlasting AC motors by 2-1/2 times
- Virtually silent - as low as <0.3 sones to maximize homeowner satisfaction
- Optional speed, built-in motion and humidity-sensing controls
- LED lighting, designer grilles and Bluetooth® speakers

CONTENTS

Introduction to Delta	2
DC Motors Explained	3
Importance of Ventilation	4
Delta Breez Promise.....	5
Certifications and Qualifications.....	6
Comprehensive Testing	7
At a Glance: Delta Breez Series Ventilation Fans	8-9
Delta BreezSignature Series	10-15
Delta BreezSmart Series	16-18
Delta BreezElite Series	19-21
Delta BreezSlim Series	22-26
Delta BreezProfessional Series	27
Delta BreezGreenBuilder Series	28-31
Delta BreezIntegrity Series	32-35
Delta BreezRadiance Series.....	36-37
Delta BreezRecessed	38
Delta Breez Fan Curves	39-43
Product Selection Guide	44-47
Equivalent Duct Lengths	48-49
Energy Saving Bathroom Solution.....	50
Frequently Asked Questions (FAQs).....	51-53

Smarter. Greener. Together.

VENTILATION RE-IMAGINED

Introduction to Delta

In 2009, Delta Breez ushered in a new era for bathroom ventilation and the Indoor Air Quality (IAQ) industry by launching a line of exhaust fans powered exclusively by DC motors – which are known for their legendary reliability, silent performance and energy-efficiency. By re-inventing the ubiquitous bath fan, we've saved consumers a lot of money on their electricity bills and enabled countless families to breathe easier.

Precision engineering lives in our DNA. In 1971, the Delta Group was founded with the mission of providing "innovative, clean and energy-efficient solutions for a better tomorrow." We are the world's largest manufacturer of brushless DC fans for all applications from consumer electronics to industrial equipment. Our footprint spans the globe with more than \$9 billion in annual revenues, 39 manufacturing facilities, 70 R&D labs and 169 sales offices. Our U.S. and Americas headquarters is located in the heart of Silicon Valley in Fremont, California.

Innovating for future generations starts today. Our commitment and vision runs deep – with a focus on developing the best and most energy-efficient solutions. In 2018, we sent shockwaves through the industry when we unveiled the market's first edge-lit LED light and bathroom fan combination. Offering consumers new choices is important for us, and Delta will only continue to push the envelope.



FOUNDED

1971

Established by Bruce Cheng in Taipei, Taiwan, to sell electronic components.



POWER SUPPLIES

1983

Mass production of switching power supplies to become the world's #1 provider.



FANS & MOTORS

1985

Mass production of brushless DC motors and fans to become the world's #1 provider.



DELTA BREEZ IAQ

2009

Global launch of bathroom ventilation fans exclusively powered by DC motors.



LED BATH FANS

2011

Adapting to changing consumer tastes and raising the bar on efficiency, Delta launched the industry's first bathroom exhaust fan and LED light combination.



DC MOTORS EXPLAINED



Reliable. Silent. Efficient. Innovative.

Legendary reliability and performance.

Each DC motor Delta Breez fan is tested to run for 70,000 hours, which is the equivalent of 8 years.

So quiet, you forget it's on.

Brushless technology and precision engineering mean near silent performance, as low as <0.3 sones – the lowest sound rating in the industry.

An energy efficiency workhorse.

Our fans use up to 74% less power than typical AC motor fans, and we exceed ENERGY STAR® requirements for efficiency by as much as 339%.

Smart fan technology protects your family.

Our proprietary lock protection system stops the fan from overheating.



**ENERGY STAR®
PARTNER OF THE YEAR
2016**

Recognizing Delta's exceptional strides in energy efficiency, the U.S. Environmental Protection Agency named Delta ENERGY STAR® Partner of the Year for the first time.



**BLUETOOTH 
2017**

Feel the rhythm and jam to your favorite tunes! Delta Breez entered the digital era with the first Bluetooth® enabled fans to stream music, sports and news.



**EDGE-LIT LED LIGHTS
2018**

On the cutting-edge of style and innovation, Delta designed the industry's first ever edge-lit LED bathroom ventilation fan. Disguised as a sleek LED light fixture, our edge-lit LED fans give any bathroom a welcome facelift and is perfect for décor enthusiasts.



**ENERGY STAR®
PARTNER-6TH YEAR
2021**

Delta was honored because of our commitment to engineer the best products that meet and surpass current standards in energy efficiency in line with the spirit of sustainability and environmental protection. Delta has won Partner of the Year for four consecutive years and was also honored with the elite "Sustained Excellence" designation in 2018, 2019, 2020, and 2021.

IMPORTANCE OF VENTILATION

Ventilation Helps You Breathe Easy

Today's homes are being built tighter than ever and are highly insulated, due to increased standards for energy efficiency in the building code. However, this can result in poor indoor air quality with unhealthy air being sealed behind windows and doors. Without adequate air exhaust, the concentration of indoor pollutants exponentially increases. Delta Breez bathroom ventilation fans help you breathe easy by exhausting the air when you need it. Our DC motor powered fans are built upon the quality and engineering expertise of nearly half a century of innovation. Ventilation is essential to improve indoor air quality. A reliable ventilation system must have the proper air flow for the designated space and be operated regularly.



Indoor Air Pollution

Indoor air pollutants are found throughout the home including combustion sources, building materials and cleaning products. Biological pollutants include mold, mildew, bacteria and pollen. Together, these pollutants can cause and exacerbate health problems, especially respiratory illnesses. High humidity and uncontrolled moisture in the home can result in higher pollutant concentrations, and increased growth of biological contaminants.



THE DELTA BREEZ PROMISE

The Path to Fresh Air

Delta Breez fans control and reduce the moisture in your home to improve indoor air quality, and minimizing the risk of health problems. High humidity conditions typically result from showering and bathing. Therefore, proper bathroom ventilation is essential to improve indoor air quality. A reliable ventilation system must have the proper air flow for the designated space and be operated regularly.



A Visionary in IAQ

Delta Breez leads the Indoor Air Quality (IAQ) industry with bathroom ventilation fans that are the gold standard for energy efficiency – saving consumers energy and money on their utility bills. All Delta Breez fans are powered by our signature brushless DC motor technology, which stands for unparalleled efficiency, legendary reliability and virtually silent operation.



CERTIFICATIONS AND QUALIFICATIONS



ENERGY STAR, a joint program of the U.S. Department of Energy and the U.S. Environmental Protection Agency, identifies products in over 60 categories which meet rigorous energy efficiency standards. Established in 1992, ENERGY STAR is an internationally recognized label for U.S.-originating products that reduce greenhouse gas emissions without sacrificing performance or quality. ENERGY STAR-qualified products protect the environment by reducing energy consumption, which also reduces greenhouse gas emissions and saves consumers money on utility bills.

As an ENERGY STAR partner, Delta strives to engineer solutions that meet and surpass current standards in energy efficiency. Delta Breez prides ourselves on delivering ENERGY STAR-qualified products, some of which exceed the ENERGY STAR efficiency requirement by 337%. With 98 ventilation fan models evaluated in 2020 , 90 (90%) models were recognized as ENERGY STAR-qualified.

For more information, visit
www.energystar.gov

ENERGY STAR Most Efficient 2021



ENERGY STAR Most Efficient is a designation that recognizes the top products for the ENERGY STAR label.

Delta Breez has 90 ENERGY STAR®-qualified bathroom fans, with some models even exceeding the criteria by 337 percent. In fact, 30 fans from the Delta BreezSignature and BreezElite lines meet the toughest efficiency criteria set by the EPA – ENERGY STAR® Most Efficient 2020.



CALGreen is a state building code requirement for California that sets baseline efficiency and sustainability standards. High efficiency products such as Delta Breez ventilation fans help builders meet this requirement.

For more information, visit
www.bsc.ca.gov/Home/CALGreen.aspx



HVI, the Home Ventilating Institute, is an organization that runs a standardized testing and certification program for a range of home ventilating products. Products are tested to qualify for various performance parameters and undergo random verification. All tests are conducted in third-party facilities that are independent of any manufacturer, while testing procedures are designed by HVI members according to internationally recognized guidelines. All Delta Breez ventilation fans are HVI lab tested and certified.

For more information about HVI, please visit: www.hvi.org



ASHRAE 62.2

ASHRAE 62.2 publishes a national standard that applies to single-family homes and multi-family dwellings to ensure proper ventilation and acceptable indoor air quality. The standard is referenced in building codes and widely accepted by architects, engineers and mechanical contractors. ASHRAE 62.2 addresses minimum ventilation effectiveness and noise level performance of continuous and intermittent mechanical exhaust systems.

The following table summarizes the ventilation air requirements in CFM for various floor areas:

Ventilation Air Requirement, CFM

Floor Area (ft²)	Bedrooms				
	0-1	2-3	4-5	6-7	>7
<1500	30	45	60	75	90
1501-3000	45	60	75	90	105
3001-4500	60	75	90	105	120
4501-5000	75	90	105	120	135
5001-7500	90	105	120	135	150
>7500	105	120	135	150	165

Most Delta Breez fan models are ASHRAE 62.2 compliant for both intermittent and continuous run applications. This means Delta Breez fans are operable according to 62.2 guidelines for airflow and meet the minimum noise level requirements.

COMPREHENSIVE TESTING ENSURES RELIABILITY


Testing procedures for ventilation fan reliability verification are conducted before, during and after production. Customers can rest easy, knowing the product's durability and long lifespan.

Design and Analysis Technology

Delta's design and analysis technology utilizes 3D and 2D tools to conduct thorough examinations during the design and production phases. Software simulations help enable the highest standards of performance.


Moldflow Analysis Software

Plastic mold




Aerodynamic Simulation Software

Fan blade curve design and air flow analysis




Structure Simulation Software

Structural analysis for stress and vibration



Semi-Anechoic Chamber

Noise testing for sound pressure and sound quality




Physical Testing for Ventilation Fan Reliability

Laboratory testing of Delta Breez products analyzes functionality and durability under harsh conditions, as well as construction for long life. The Basic Function Test checks current, speed and noise. The Safety Test includes leakage current, Hipot (high potential), ground bond and insulation testing. Comprehensive reliability testing continues with:

- Low Temperature and High Temp/Rating Voltage on/off Test
- Temperature Cycling and Power Switching
- Impeller Locked Test
- Thermal Shock
- Humidity Exposure
- Water Spray
- Random Vibration and Drop (packing)
- Operational and Non-operational Vibration
- Mechanical Shock
- Life Test

Brushless DC Motor Fan Highlights





Delta Breez Series Ventilation Fans

DeltaBreez is the only residential bathroom exhaust fan manufacturer that can deliver a powerful combination of ENERGY STAR®-qualification, performance, quietness, state-of-the-art brushless DC motor technology and affordability in every fan. Optional built-in speed, motion and/or humidity-sensing controls — plus decorative or edge-lit dimmable LED lighting, heater, designer fan grille and Bluetooth® speakers, to satisfy consumer preferences and building codes.

Choose from nine different series:



Virtually silent, feature-rich. One of our highest performing, most quiet series at less than 0.3 sones. High speed 80 or 110 CFM. For spaces 80-110 sq. ft. Options include adjustable high and/or low speeds, dimmable LED light or dimmable edge-lit LED light, motion and/or adjustable humidity sensor, Bluetooth® speaker. Ceiling Radiation Damper, designer grille, and metal grille available separately. UL listed for ceiling mount only.



Virtually silent, feature-rich. One of our highest performing, most quiet series at less than 0.3 sones. High speed 130 or 150 CFM. For spaces 130-150 sq. ft. Options include adjustable low speeds, LED light, motion or adjustable humidity sensor. Ceiling Radiation Damper and metal grille available separately. UL listed for ceiling mount only.




Affordable performance, feature-rich with very quiet operation from 0.5 to 0.7 sones. Innovative, pocket mounting brackets stay hidden and slide out for room-side installation in remodeling projects and for time-saving installation in new construction projects, a solution where space is at a premium. High speed 80 or 110 CFM. For spaces 80-110 sq. ft. Options include adjustable high and/or low speeds, dimmable LED light, motion and/or adjustable humidity sensor. Ceiling Radiation Damper available. UL listed for ceiling mount only.



Builders' best solution. High speed 80 or 100 CFM. For spaces 80-100 sq. ft. Quiet operation from 0.8 to 1.5 sones. Options include adjustable low speed, dimmable LED light, and decorative LED light, motion and/or humidity sensor. Ceiling Radiation Damper and designer grille available separately. Fans only and fans with humidity sensor are UL listed for ceiling and wall mount; fans/LED light are UL listed for ceiling mount only.



Economical solution. Single speed 50, 80 or 100 CFM. For spaces 50-100 sq. ft. Quiet operation from 0.7 to 1.5 sones. Options include dimmable LED light or dimmable edge-lit LED light, adjustable humidity sensor, Bluetooth® speaker. Ceiling Radiation Damper and designer grille available separately. Fans only and fan with humidity sensor are UL listed for ceiling and wall mount; fans/LED light are UL listed for ceiling mount only.



breez Slim

Ultimate multi-family solution. Single speed 50, 70, 80, 100, dual speed 70, and high speed 80 or 110CFM. For spaces 50-110 sq. ft. Quiet operation from 0.4 to 2.0 sones. Options include adjustable high and/or low speeds, dimmable LED light, dual speed or built-in humidity sensor. Low profile, with 4" depth to fit between ceiling joists and 2x4 sidewalls. Designer grille available separately for SLM50, SLM70, SLM70D and SLM70H. Ceiling Radiation Damper available separately for SLM80, SLM100. UL listed for ceiling and wall mount.

breez Recessed


Fan design solution. 80 CFM fan disguised as a recessed light with LED main and night light. For 80 sq. ft. space. Quiet operation at 1.5 sones. UL approved for ceiling mount only.

breez Radiance

Fan/heater solution to warm and delight. Quiet operation from 0.7 to 1.5 sones. 80 or 110 CFM for spaces 80-110 sq. ft. Options include CFL or dimmable LED light, or fan/heater only. Built-in thermostat to regulate room temperature for maximum comfort. UL approved for ceiling mount only.

breez Pro

Large space solution. Single speed 200 or 300 CFM. Quiet operation from 1.0 to 2.0 sones. For spaces 200-300 sq. ft. Perfect for large bathrooms, laundry rooms, and conference rooms. UL approved for ceiling mount only.





6 Inch Duct Series

Virtually silent, feature-rich. Our highest performing, most quiet series at less than 0.3 sones.

High speed 80 or 110 CFM. For spaces 80-110 sq. ft. Options include adjustable high and/or low speeds, dimmable LED light or edge-lit dimmable LED light, motion and/or adjustable humidity sensor. Ceiling Radiation Damper, designer grille, and metal grille available separately. UL listed for ceiling mount only.

Features:

- Energy savings up to 127% ¹ and 6" metal duct
- <0.3 sones - lowest noise level among competing fans
- Exceeds ENERGY STAR requirement by 450% in energy efficiency ²
- Adjustable high speed of 80 or 110 CFM
- Dual speed, motion-sensing and humidity-sensing options with continuous adjustable low-speed
- Includes 6" to 4" duct reducer

Fan/Dimmable LED Light:

- 13-Watt LED main light and 2-Watt LED night light
- Main light output of 850 lumens, 3000K and 90 CRI
- Dimmable LED light (dimmer switch not included)

Fan/Edge-Lit Dimmable LED Light with Adjustable Color Temperature 2700K, 4000K and 5000K

- 13-Watt LED main light output 1000 lumens

1. Based upon SIG80-110 vs. market AC motor.

2. Based upon SIG 80 CFM vs. ENERGY STAR v4.0 criteria for residential ventilating fans



Fan only and Fan with Humidity Sensor or Dual Speed



Fan/Edge-lit Dimmable LED Light

- 2700K
 - 4000K
 - 5000K
- CCT Switch



Fan/ Dimmable LED Light/ Night-Light
(Options: Fan with Dual Speed, Humidity Sensor or Motion Sensor)






High Speed Switch




Adapter 4 inches




BreezSignature Series Dimensions



SIG80-110H
SIG80-110HLED
SIG80-110MH
SIG80-110MHLED
Controls



SIG80-110D
SIG80-110DLED
Controls



SIG80-110MHLED
Motion
Controls



LED Indicator Light:
SIG80-110,
SIG80-110LED



LED Indicator Light: SIG80-110D
Continuous
Low Speed Full Speed



LED Indicator Light: SIG80-110H, SIG80-110HLED,
SIG80-110MH

Humidity Sensing




Full Speed




LED Indicator Light: SIG80-110DLED

Low Speed



Full Speed



LED Indicator Light: SIG80-110MHLED

Low Speed



Full Speed



	Delta Breez	Market AC Motor
Energy Use (Watts)	6.2	31.4
Noise Level (Sones)	<0.3	0.7
Annual Energy Cost per Fan (24/7) ¹	\$6.50	\$33.03

1. Calculations based upon U.S. average retail electricity. Actual results may vary

Specifications

SIG80-110 - 80/110 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	110
Sones	<0.3	0.5	<0.3	0.8
Power Consumption (Watts)	6.2	9.9	8.2	14.1
Energy Efficiency (CFM/Watts)	15.4	9.0	15.3	8.7
Current (Amps)	0.38 Max			
Power Rating (V/Hz)	120/60			



6 Inch Duct Series Specifications

SIG80-110ELED - 80/110 CFM



Fan/Edge-lit Dimmable LED Light w/ adjustable color temperature

Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	109
Sones	<0.3	0.8	0.5	1.0
Power Consumption (Watts)	7.5	11.5	9.9	15.5
Energy Efficiency (CFM/Watts)	11.7	7.6	11.8	7.3
Current (Amps)	0.48 Max			
Power Rating (V/Hz)	120/60			
LED Main Light (Watts)	13			

SIG80-110LED - 80/110 CFM



Fan/Dimmable LED Light/Night-Light

Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	110
Sones	<0.3	0.5	<0.3	0.8
Power Consumption (Watts)	6.8	9.9	9.7	15.5
Energy Efficiency (CFM/Watts)	13.8	8.4	12.7	8.0
Current (Amps)	0.48 Max			
Power Rating (V/Hz)	120/60			
LED Main Light (Watts)	13			
LED Night Light (Watts)	2			

SIG80-110D - 80/110 CFM Fan with Dual Speed



Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.3	4.8	7.3	5.5	8.6	6.2	9.9	6.2	9.9	8.2	14.1
Efficiency (CFM/Watts)	9.0	5.9	13.5	8.0	13.3	8.0	15.4	9.0	15.4	9.0	15.3	8.7
Current (Amps)	0.38 Max											
Power Rating (V/Hz)	120/60											

SIG80-110DLED - 80/110 CFM



Fan/Dimmable LED Light/Night-Light with Dual Speed

Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.7	5.2	8.2	5.6	8.7	6.8	9.9	6.8	9.9	9.7	15.5
Efficiency (CFM/Watts)	9.5	5.8	12.3	7.1	13.2	8.0	13.8	8.4	13.8	8.4	12.7	8.0
Current (Amps)	0.48 Max											
Power Rating (V/Hz)	120/60											
LED Main Light (Watts)	13											
LED Night Light (Watts)	2											

SIG80-110H - 80/110 CFM Fan with Humidity Sensor



Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.3	4.8	7.3	5.5	8.6	6.2	9.9	6.2	9.9	8.2	14.1
Efficiency (CFM/Watts)	9.0	5.9	13.5	8.0	13.3	8.0	15.4	9.0	15.4	9.0	15.3	8.7
Current (Amps)	0.38 Max											
Power Rating (V/Hz)	120/60											

SIG80-110HLED - 80/110 CFM



Fan/Dimmable LED Light/Night-Light with Humidity Sensor

Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.7	5.2	8.2	5.6	8.7	6.8	9.9	6.8	9.9	9.7	15.5
Efficiency (CFM/Watts)	9.5	5.8	12.3	7.1	13.2	8.0	13.8	8.4	13.8	8.4	12.7	8.0
Current (Amps)	0.48 Max											
Power Rating (V/Hz)	120/60											
LED Main Light (Watts)	13											
LED Night Light (Watts)	2											

SIG80-110MH - 80/110 CFM



Fan with Motion and Humidity Sensor

Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.3	4.8	7.3	5.5	8.6	6.2	9.9	6.2	9.9	8.2	14.1
Efficiency (CFM/Watts)	9.0	5.9	13.5	8.0	13.3	8.0	15.4	9.0	15.4	9.0	15.3	8.7
Current (Amps)	0.38 Max											
Power Rating (V/Hz)	120/60											


SIG80-110MHLED - 80/110 CFM



Fan/Dimmable LED Light/Night-Light w/ Motion and Humidity Sensor

Fan Speed	Continuous Low Speed								Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	30	50	50	60	60	80	80	80	80	110	110
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5	<0.3	0.5	<0.3	0.8
Power (Watts)	4.4	6.7	5.2	8.2	5.6	8.7	6.8	9.9	6.8	9.9	9.7	15.5
Efficiency (CFM/Watts)	9.5	5.8	12.3	7.1	13.2	8.0	13.8	8.4	13.8	8.4	12.7	8.0
Current (Amps)	0.48 Max											
Power Rating (V/Hz)	120/60											
LED Main Light (Watts)	13											
LED Night Light (Watts)	2											

4 Inch Duct Series



LED Indicator Light:
SIG80 and SIG110




LED Indicator Light:
SIG80D
Continuous
Low Speed



Full Speed



SIG80D
Controls



Specifications

SIG80 - 80 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	79
Sones	<0.3	0.5
Power Consumption (Watts)	8.7	14.0
Energy Efficiency (CFM/Watts)	9.7	6.3
Current (Amps)	0.30 Max	
Power Rating (V/Hz)	120/60	

SIG80D - 80 CFM Dual Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	30	31	50	50	60	61	80	79
Sones	<0.3	<0.3	<0.3	<0.3	<0.3	0.3	<0.3	0.5
Power Consumption (Watts)	4.8	8.9	6.6	9.8	6.7	11.8	8.7	14.0
Energy Efficiency (CFM/Watts)	7.7	4.1	8.4	5.2	9.9	5.6	9.7	6.3
Current (Amps)	0.30 Max							
Power Rating (V/Hz)	120/60							

SIG110 - 110 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	110	95
Sones	<0.3	0.6
Power Consumption (Watts)	13.6	16.0
Energy Efficiency (CFM/Watts)	9.0	6.4
Current (Amps)	0.38 Max	
Power Rating (V/Hz)	120/60	

	Delta Breez	Market AC Motor
Energy Use (Watts)	8.7	28.4
Noise Level (Sones)	<0.3	0.8
Annual Energy Cost per Fan (24/7) ¹	\$9.15	\$29.94

1. Calculations based upon U.S. average retail electricity. Actual results may vary




4 Inch Duct Series

VFB25ADBT 110 CFM Fan with Bluetooth® stereo speaker enables you to enjoy your favorite music, or listen to news, weather, traffic or sports while the energy-efficient fan quietly ventilates your bathroom. Easily pairs with most Bluetooth wireless devices. Quiet operation at 1.0 sone, so you hear your entertainment, not the fan.

Features:

Long-lasting, brushless DC motor engineered to operate minimum 70,000 hours.

- Includes a built-in Bluetooth 2.1, Stereo Speaker 4 ohm 2W x 2
- Play audio through most Bluetooth wireless devices
- Attractive grille complements any décor



Fan with Bluetooth®

Specifications

VFB25ADBT - 110 CFM Fan with Bluetooth



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	110	81
Sones	1.0	1.5
Power Consumption (Watts)	14.2	15.0
Energy Efficiency (CFM/Watts)	7.7	5.3
Current (Amps)	0.3 @ 110Vac	
Power Rating (V/Hz)	110~220/50~60	

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by Delta Electronics, Inc. is under license. Other trademarks and trade names are those of their respective owners.

	Delta Breez	Market AC Motor
Energy Use (Watts)	14.2	34
Noise Level (Sones)	1.0	1.5
Annual Energy Cost per Fan (24/7) ²	\$14.94	\$35.91

1. Based upon ENERGY STAR criteria for residential ventilating fans.


2. Based upon BreezSignature VFB25ACH vs. market AC motor fan.

Ceiling Radiation Damper SIG-CRD

The damper employs a folded curtain style blade for point-of-origin control of radiant heat in a ventilation system. SIG-CRD installs in the ceiling membrane for floor/ceiling or roof/ceiling assemblies with a fire resistance rating up to and including 3 hours.

Features:

- UL listed as fan/damper assembly for the following Wood Frame Construction designs: L521, L546, L558, L562, L574, L576, L581, L583, L585, P522, P533, P538 and P545
- Meets both UL555C and UL263. UL and cUL listed and exceeds UL 555C for use in 3-hour fire rated assemblies
- Warnock-Hersey certified for use in fire rated floor ceiling or roof/ceiling assemblies. Warnock Hersey listing #: 102195501SAT-002
- CSFM listing: 3226-0368:104
- UL 555C listing: R27832
- Meets NFPA Standards: 90A and 101
- Meets Building Code Standards: IBC, NBC, NFPA, SBC, & UBC
- Available for use with Delta Breez SIG Series ventilation fans




Metal Grille SIG-MTL

The SIG-MTL metal grille is offered as an alternative to the standard grille on Delta Breez SIG80, SIG80D, SIG110, SIG80-110, SIG80-110D, SIG80-110H.

Features:

- Adds modern aesthetic to bathroom
- Made of galvanized steel material and painted white
- Paintable for added customization
- Size: 13 x 13 x 3/8 inches




Designer Grille SIG-DGL

The SIG-DGL designer fan grille is offered as an alternative to the standard grille on Delta Breez SIG80, SIG80D, SIG110, SIG80-110, SIG80-110D, SIG80-110H

Features:

- Adds modern aesthetic to bathroom
- Made of long lasting ABS material
- Paintable to coordinate with any style bathroom
- Size: 12 3/8" x 12 3/8"





Fans with adjustable high speed options
(150-200 CFM)

6 Inch Duct Series

The Smart Choice. Virtually silent, feature-rich.

Delta BreezSmart Series is the perfect ventilation solution for today's larger, spa-style bathrooms. One of our highest performing, most quiet at less than 0.3 sones. High speed 130 or 150 CFM, or adjustable high speed 150-200 CFM. For spaces 130-200 sq. ft. Options include adjustable low speeds, LED light, motion or adjustable humidity sensor. Ceiling Radiation Damper and metal grille available separately. UL listed for ceiling mount only.

Features:

- Energy savings up to 57.9% ¹
- <0.3 sones - lowest noise level among competing fans
- Exceeds ENERGY STAR requirement by 151% in energy efficiency ²
- Motion-sensing, humidity-sensing, LED and dual-speed options available with user-adjustable continuous low speed

Fan/Dimmable LED light:

- 13-Watt LED main light and 2-Watt LED night light
- Main light output of 850 Lumens, 3000K and 90 CRI Dimmable LED Light (dimmer switch not included)

¹. Based upon BreezSmart SMT150-200 (200 CFM) vs. market AC motor fan

². Based upon SMT 150 CFM vs. ENERGY STAR v4.0 criteria for residential fans

	Delta Breez	Market AC Motor
Energy Use (Watts)	24	57
Noise Level (Sones)	1.0	1.2
Annual Energy Cost per Fan (24/7) ³	\$24.67	\$58.59

³. Calculations based upon U.S. average retail electricity. Actual results may vary



High Speed Switch

Fan/Dimmable
LED Light

- 3000K
- 4000K
- 5000K



LED
DIMMABLE




High Speed Fans (130 CFM or 150 CFM)



LED
DIMMABLE



LED Indicator Light: SMT130, SMT150, SMT150LED,
SMT150-200, & SMT150-200LED



LED Indicator Light: SMT130M, SMT150D
Continuous Low Speed Full Speed




LED Indicator Light: SMT130H
Humidity Sensing Full Speed




Built-in Controls


SMT130H Controls




SMT130M Controls




SMT150D Controls




BreezSmart Series Dimensions




Fan Grille



Fan/Dimmable
LED Light Grille




Fan Grille



Fan/Dimmable
LED Light Grille

BreezSmart Series Dimensions



Fan Housing



Specifications

SMT130* - 130 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	130	124
Sones	<0.3	1.0
Power Consumption (Watts)	11.6	20.0
Energy Efficiency (CFM/Watts)	11.2	6.2
Current (Amps)	0.44 Max	
Power Rating (V/Hz)	120/60	

SMT130H* - 130 CFM with Humidity Sensor



Fan Speed	Continuous Low Speed						Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	49	70	68	90	88	130	124
Sones	<0.3	1.0	<0.3	1.0	<0.3	1.0	<0.3	1.0
Power Consumption (Watts)	5.6	12.2	6.9	13.5	8.0	15.5	11.6	20.0
Energy Efficiency (CFM/Watts)	8.9	4.0	10.1	5.0	11.2	5.6	11.2	6.2
Current (Amps)	0.44 Max							
Power Rating (V/Hz)	120/60							

SMT130M* - 130 CFM with Motion Sensor



Fan Speed	Continuous Low Speed						Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	49	70	68	90	88	130	124
Sones	<0.3	1.0	<0.3	1.0	<0.3	1.0	<0.3	1.0
Power Consumption (Watts)	5.6	12.2	6.9	13.5	8.0	15.5	11.6	20.0
Energy Efficiency (CFM/Watts)	8.9	4.0	10.1	5.0	11.2	5.6	11.2	6.2
Current (Amps)	0.44 Max							
Power Rating (V/Hz)	120/60							

SMT150 - 150 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	150	149
Sones	<0.3	1.3
Power Consumption (Watts)	16.9	23.7
Energy Efficiency (CFM/Watts)	8.8	6.2
Current (Amps)	0.47 Max	
Power Rating (V/Hz)	120/60	

SMT150D - 0-110/150 CFM Fan

Adjustable Dual Speed



Fan Speed	Continuous Low Speed						Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	70	68	90	88	110	109	150	149
Sones	<0.3	1.0	<0.3	1.0	<0.3	1.0	<0.3	1.3
Power Consumption (Watts)	6.9	13.5	8.0	15.5	9.8	18.4	16.9	23.7
Energy Efficiency (CFM/Watts)	10.1	5.0	11.2	5.6	11.2	5.9	8.8	6.2
Current (Amps)	0.47 Max							
Power Rating (V/Hz)	120/60							

SMT150LED - 150 CFM

Fan/Dimmable LED Light/ Night-Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	150	150
Sones	0.5	1.3
Power Consumption (Watts)	17.6	25.4
Energy Efficiency (CFM/Watts)	8.5	5.9
Current (Amps)	0.62 Max	
Power Rating (V/Hz)	120/60	
LED Main Light (Watts)	13	
LED Night Light (Watts)	2	

SMT150-200 - 150/200 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	150	150	200	200
Sones	0.4	1.3	1.0	1.5
Power Consumption (Watts)	14.0	22.0	24.0	36.0
Energy Efficiency (CFM/Watts)	10.7	6.8	8.3	5.5
Current (Amps)	0.68 Max			
Power Rating (V/Hz)	120/60			

SMT150-200LED - 150/200 CFM Fan/

Dimmable LED Light w/ adjustable color temperature



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	150	150	200	200
Sones	0.6	1.3	1.0	1.5
Power Consumption (Watts)	15.0	23.0	25.0	37.0
Energy Efficiency (CFM/Watts)	10.0	6.5	8.0	5.4
Current (Amps)	0.78 Max			
Power Rating (V/Hz)	120/60			
LED Main Light (Watts)	13			


* Product is ENERGY STAR Most Efficient 2021 distinction and ENERGY STAR qualified

Ceiling Radiation Damper SMT-CRD

The damper employs a folded curtain style blade for point-of-origin control of radiant heat in a ventilation system. SMT-CRD installs in the ceiling membrane for floor/ceiling or roof/ceiling assemblies with a fire resistance rating up to and including 3 hours.

Features:

- UL and cUL listed and exceeds UL 555C for use in 3-hour fire rated assemblies
- Warnock-Hersey certified for use in fire rated floor/ceiling or roof/ceiling assemblies
- CSFM listing: 3226-0368:104
- Meets NFPA Standards: 90A and 101
- Meets Building Code Standards: IBC, NBC, NFPA, SBC, and UBC
- Available Available for use with Delta Breez SMT130, SMT130M, SMT130H, SMT150, SMT150D, and SMT150LED (For combustible and non-combustible installation), SLM80, SLM100, SLM80-110-C, SLM80-110LED-C, SLM80-110D-C, and SLM80-110DLED-C (For non-combustible installation only).





Delta BreezSmart SMT-MTL Metal Grille

The The SMT-MTL metal grille is offered as an alternative to the standard grille on Delta Breez SMT130, SMT130H, SMT150, SMT150D, SMT150-200, SLM80 and SLM100.

Features:

- Adds modern aesthetic to bathroom
- Made of galvanized steel material and white painted
- Paintable for added customization
- Size: 13 x 13 x 3/8 inches





Delta BreezElite Series (6" duct)

Affordable performance, feature-rich with very quiet operation from 0.5 to 0.7 sones.

Innovative, pocket mounting brackets stay hidden and slide out for room-side installation in remodeling projects and for time-saving installation in new construction projects. A perfect solution where space is at a premium. High speed 80 or 110 CFM. For spaces 80-110 sq ft. Options include adjustable high and/or low speeds, dimmable LED light, motion and/or adjustable humidity sensor. Ceiling Radiation Damper available. UL listed for ceiling mount only.

Features:

- Innovative brushless DC motor design for long life, low noise, and low power consumption
- Energy savings up to 67.1 %¹ and 6" duct (standard)
- Lowest sone level rated by HVI as low as 0.7 sones
- *Adjustable wings for easy installation*
- Power consumption down to 10.3 Watts
- Exceeds ENERGY STAR requirement by 202 % in energy efficiency²
- Adjustable high speed of 80 or 110 CFM
- Dual speed, motion-sensing, and humidity-sensing options with continuous adjustable low-speed
- Includes 6" to 4" duct reducer
- Ceiling Radiation Damper available (fits GBR-CRD)

Fan/Dimmable LED Light:

- 13-Watt LED light output of 850 lumens, 3000K and 90CRI
- Dimmable LED light (dimmer switch not included)

pocket mounting brackets stay hidden



pocket mounting brackets slide out



Adapter 4" duct




High Speed Switch

1. Based upon ELT80-110 vs. market AC motor with 6" duct.


2. Based upon ELT 110 CFM vs. ENERGY STAR v4.0 criteria for residential ventilating fans




BreezElite Series Dimensions



Fan/Dimmable
LED Light Grille




Fan Grille




Built-in Controls

ELT80-110H, ELT80-110HLED
ELT80-110MH, ELT80-110MHLED




ELT80-110D
ELT80-110DLED




LED Indicator Light:

ELT80-110, ELT80-110LED



ELT80-110D, ELT80-110DLED

Low Speed




Full Speed




ELT80-110H, ELT80-110HLED,
ELT80-110MH and ELT80-110MHLED

Humidity Sensing



Full Speed



Specifications

ELT80-110 - 80/110 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	59	110	90
Sones	0.5	0.9	0.7	1.0
Power Consumption (Watts)	7	9	10.3	13
Energy Efficiency (CFM/Watts)	11.4	6.5	10.6	6.9
Current (Amps)	0.27 Max			
Power Rating (V/Hz)	120/60			

ELT80-110LED - 80/110 CFM Fan
Fan/Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	59	110	89
Sones	0.5	0.9	0.7	1.0
Power Consumption (Watts)	7	9	10.3	13
Energy Efficiency (CFM/Watts)	11.4	6.5	10.6	6.8
Current (Amps)	0.28 Max			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			



Specifications (cont.)

ELT80-110D - 80/110 CFM Fan w/ Dual Speed



Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	32	80	59	80	59	110	90
Sones	<0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10	5.3	11.4	6.5	11.4	6.5	10.6	6.9
Current (Amps)	0.27 Max							
Power Rating (V/Hz)	120/60							

ELT80-110DLED - 80/110 CFM Fan/Dimmable LED light w/ Dual Speed



Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	35	80	59	80	59	110	89
Sones	0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10.0	5.8	11.4	6.5	11.4	6.5	10.6	6.8
Current (Amps)	0.28 Max							
Power Rating (V/Hz)	120/60							
Dimmable LED Light (Watts)	13							

ELT80-110HLED - 80/110 CFM Fan/Dimmable LED Light with Humidity Sensor



Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	35	80	59	80	59	110	89
Sones	0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10	5.8	11.4	6.5	11.4	6.5	10.6	6.8
Current (Amps)	0.28 Max							
Power Rating (V/Hz)	120/60							
Dimmable LED Light (Watts)	13							

ELT80-110H - 80/110 CFM Fan w/ Humidity Sensor



Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	32	80	59	80	59	110	90
Sones	<0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10	5.3	11.4	6.5	11.4	6.5	10.6	6.9
Current (Amps)	0.27 Max							
Power Rating (V/Hz)	120/60							

ELT80-110MH - 80/110 CFM Fan w/ Motion and Humidity Sensor




Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	32	80	59	80	59	110	90
Sones	<0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10	5.3	11.4	6.5	11.4	6.5	10.6	6.9
Current (Amps)	0.27 Max							
Power Rating (V/Hz)	120/60							

ELT80-110MHLED - 80/110 CFM Fan/Dimmable LED Light w/ Motion and Humidity Sensor



Fan Speed	Continuous Low Speed				Full Speed			
Static Pressure (in w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	35	80	59	80	59	110	89
Sones	0.3	0.8	0.5	0.9	0.5	0.9	0.7	1.0
Power (Watts)	5	6	7	9	7	9	10.3	13
Efficiency (CFM/Watts)	10	5.8	11.4	6.5	11.4	6.5	10.6	6.9
Current (Amps)	0.28 Max							
Power Rating (V/Hz)	120/60							
Dimmable LED Light (Watts)	13							



¹ Calculations based upon U.S. average retail electricity. Actual results may vary



4 Inch Duct Series

Fan design solution.



80 CFM fan disguised as a recessed light with Dimmable LED. For 80 sq. ft. space. Quiet operation at 1.5 sones. UL approved for ceiling mount only.

Features:

- ENERGY STAR qualified
- Brushless DC motor lasts 70,000 hours for extended reliability
- Quiet Operation at 1.5 sones

Fan/Dimmable LED Light:

- 13-Watt Dimmable LED light included (dimmer switch not included)
- LED main light output 850 lumens, 3000K, and 90 CRI



	Delta Breez	Market AC Motor
Energy Use (Watts)	14.5	34.4
Noise Level (Sones)	1.5	1.5
Annual Energy Cost per Fan (24/7) ¹	\$15.25	\$35.91

¹ Calculations based upon U.S. average retail electricity. Actual results may vary

Specifications

REC80LED - 80 CFM Fan/Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	65
Sones	1.5	2.0
Power Consumption (Watts)	14.5	14.5
Energy Efficiency (CFM/Watts)	6.1	5.4
Current (Amps)	0.34 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watts)	13	



4 Inch Oval Duct Series

The BreezSlim series of fans are suitable for ceiling or sidewall installation with high speed 80 or 110 CFM.

For spaces 80-110 sq. ft. Delta Breez Slim models offer a 4" metal oval duct and 4 side flange housing. Delta BreezSlim options include single speed, dimmable LED light, and/or dual speed. UL listed for wall and ceiling mount. Available in contractor packs.

Features:

Slim design with innovative brushless DC motor design for long life, low noise, and low power consumption.

- 4" Oval Duct:
 - Noise level at down to 1.2 sones
 - Annual energy cost for 24/7 operation is approximately \$8.94¹ (80 CFM) or \$17.35¹ (110 CFM)
 - Ultra low power consumption down to 8.5 Watts
- UL approved for ceiling and wall mount installation
- Green and amber LED indicator lights show continuous low speed and full speed modes

Fan/Dimmable LED light:

- 13-Watt LED light output of 850 Lumens, 3000K and 90 CRI
- Dimmable LED Light (dimmer switch not included)

	Delta Breez	Market AC Motor
Energy Use (Watts)	8.5	30.6
Noise Level (Sones)	0.4	1.5
Annual Energy Cost per Fan (24/7) ²	\$8.94	\$32.2

1. Based upon SLM80-110 vs. market AC motor.

2. Calculations based upon U.S. average retail electricity. Actual results may vary



Fan/Dimmable LED Light



Fan Only




Project Pack Components Available



High Speed Switch

LED Indicator Light:



SLM80-110
SLM80-110LED




SLM80-110D, SLM80-110DLED
Low Speed Full Speed



BreezSlim Series Dimensions




Fan/Dimmable
LED Light Grille



Fan Grille

Built-in control
SLM80-110D
SLM80-110DLED



Specifications

SLM80-110 - 80/110 CFM Single Speed Fan



	Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	110
Sones	0.4	1.0	1.2	1.5
Power Consumption (Watts)	8.5	14.5	16.5	24
Energy Efficiency (CFM/Watts)	9.4	5.5	6.6	4.5
Current (Amps)	0.6 Max.			
Power Rating (V/Hz)	120/60			
Project Pack Components Available SLM-A3 (housing) and SLM80-110-B (motor and grille)				

SLM80-110D - 80/110 CFM Fan with Dual Speed



	Continuous low speed				Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	50	80	80	80	80	110	110
Sones	<0.3	0.8	0.4	1.0	0.4	1.0	1.2	1.5
Power Consumption (Watts)	6	9.5	8.5	14.5	8.5	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.3	5.2	9.4	5.5	9.4	5.5	6.6	4.5
Current (Amps)	0.6 Max.							
Power Rating (V/Hz)	120/60							

SLM80-110LED - 80/110 CFM

Fan/Dimmable LED Light



	Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	106
Sones	0.4	1.1	1.3	1.5
Power Consumption (Watts)	9.0	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.8	5.5	6.6	4.4
Current (Amps)	0.6 Max.			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			
Project Pack Components Available SLMLED-A3 (housing) and SLM80-110LED-B (motor and LED grille)				

SLM80-110DLED - 80/110 CFM

Fan/Dimmable LED Light with Dual Speed



	Continuous low speed				Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	47	80	80	80	80	110	106
Sones	<0.3	0.8	0.4	1.1	0.4	1.1	1.3	1.5
Power Consumption (Watts)	6	9.5	9.0	14.5	9.0	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.3	4.9	8.8	5.5	8.8	5.5	6.6	4.4
Current (Amps)	0.6 Max.							
Power Rating (V/Hz)	120/60							
Dimmable LED Light (Watts)	13							



4 Inch Oval Duct Series G3-C can fit with Ceiling Radiation Damper SMT-CRD

The BreezSlim series of fans are suitable for ceiling or sidewall installation with high speed 80 or 110 CFM.

For spaces 80-110 sq. ft. Delta Breez Slim models offer a 4" metal oval duct adapter. Delta BreezSlim options include single speed, dimmable LED light, and/or dual speed. UL listed for wall and ceiling mount. Available in contractor packs.

Features:

Slim design with innovative brushless DC motor design for long life, low noise, and low power consumption.

- 4" Oval Duct:
 - Noise level at down to 1.2 sones
 - Annual energy cost for 24/7 operation is approximately \$8.94¹ (80 CFM) or \$17.35¹ (110 CFM)
 - Ultra low power consumption down to 8.5 Watts
- UL approved for ceiling and wall mount installation
- Green and amber LED indicator lights show continuous low speed and full speed modes

Fan/Dimmable LED light:

- 13-Watt LED light output of 850 Lumens, 3000K and 90 CRI
- Dimmable LED Light (dimmer switch not included)

	Delta Breez	Market AC Motor
Energy Use (Watts)	8.5	30.6
Noise Level (Sones)	0.4	1.5
Annual Energy Cost per Fan (24/7) ²	\$8.94	\$32.2

1. Based upon SLM80-110-C vs. market AC motor.

2. Calculations based upon U.S. average retail electricity. Actual results may vary



Fan/Dimmable LED Light




Fan Only




Project Pack
Components
Available

LED Indicator Light:



SLM80-110-C
SLM80-110LED-C




SLM80-110D-C, SLM80-110DLED-C
Low Speed Full Speed



BreezSlim Series Dimensions



Fan/Dimmable
LED Light Grille




Fan Grille



High Speed
Switch

Built-in control
SLM80-110D-C
SLM80-110DLED-C



Specifications

SLM80-110-C - 80/110 CFM Single Speed Fan



	Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	110
Sones	0.4	1.0	1.2	1.5
Power Consumption (Watts)	8.5	14.5	16.5	24
Energy Efficiency (CFM/Watts)	9.4	5.5	6.6	4.5
Current (Amps)	0.6 Max.			
Power Rating (V/Hz)	120/60			

SLM80-110D-C - 80/110 CFM Fan with Dual Speed



	Continuous low speed				Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	50	80	80	80	80	110	110
Sones	<0.3	0.8	0.4	1.0	0.4	1.0	1.2	1.5
Power Consumption (Watts)	6	9.5	8.5	14.5	8.5	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.3	5.2	9.4	5.5	9.4	5.5	6.6	4.5
Current (Amps)	0.6 Max.				0.6 Max.			
Power Rating (V/Hz)	120/60				120/60			

SLM80-110LED-C - 80/110 CFM Fan/Dimmable LED Light



	Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	80	80	110	106
Sones	0.4	1.1	1.3	1.5
Power Consumption (Watts)	9.0	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.8	5.5	6.6	4.4
Current (Amps)	0.6 Max.			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			

SLM80-110DLED-C - 80/110 CFM Fan/Dimmable LED Light with Dual Speed



	Continuous low speed				Full speed			
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	47	80	80	80	80	110	106
Sones	<0.3	0.8	0.4	1.1	0.4	1.1	1.3	1.5
Power Consumption (Watts)	6	9.5	9.0	14.5	9.0	14.5	16.5	24
Energy Efficiency (CFM/Watts)	8.3	4.9	8.8	5.5	8.8	5.5	6.6	4.4
Current (Amps)	0.6 Max.				0.6 Max.			
Power Rating (V/Hz)	120/60				120/60			
Dimmable LED Light (Watts)	13				13			



4 Inch Oval Duct Series

The BreezSlim series of fans are suitable for ceiling or sidewall installation.

All BreezSlim fans are ENERGY STAR qualified. Delta Breez SLM80 and SLM100 models offer a 4" metal oval duct adapter. As with all Delta Breez fans, BreezSlim series fans also feature an LED indicator light underneath the grille to show the user that this quiet fan is running. Available in contractor packs.


Features:

Slim design with innovative brushless DC motor design for long life, low noise, and low power consumption


- 4" Oval Duct:
 - Noise level at down to 0.7 sones
 - Annual energy cost for 24/7 operation is approximately \$8.94¹
 - Ultra low power consumption down to 8.5 Watts
- UL approved for ceiling and wall mount installation
- Ceiling Radiation Damper available (fits SMT-CRD)

	Delta Breez	Market AC Motor
Energy Use (Watts)	8.5	25.7
Noise Level (Sones)	0.7	1.1
Annual Energy Cost per Fan (24/7) ²	\$8.94	\$27.02

LED Indicator Light:
SLM80, SLM100



4" Oval duct



Fan Grille

Specifications

SLM80 - 80 CFM Single Speed Exhaust Fan



	4" Oval duct	
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	62
Sones	0.7	1.1
Power Consumption (Watts)	8.5	10.9
Energy Efficiency (CFM/Watts)	9.4	5.6
Current (Amps)	0.26 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available SLM-A2 (housing) and SLM80-B (motor and grille)		

SLM100 - 100 CFM Single Speed Exhaust Fan



	4" Oval duct	
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	84
Sones	1.0	1.5
Power Consumption (Watts)	14.5	17.7
Energy Efficiency (CFM/Watts)	6.8	4.7
Current (Amps)	0.3 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available SLM-A2 (housing) and SLM100-B (motor and grille)		



1. Based upon SLM80 CFM vs. ENERGY STAR v4.0 criteria for residential ventilating fans
2. Calculations based upon U.S. average retail electricity. Actual results may vary



3 Inch Duct Series

Super Low Profile. Super Low Energy Consumption.

Weighing less than 5 lbs., the powerful and compact Delta BreezSlim sets the bar for performance in the popular small fan size of 7 1/2" x 7 1/4" x 4". Operating at just 1.0 sone, this quiet fan features Delta's super reliable brushless DC motor, an LED indicator light so you know it's running, and a modern grille design. Perfect for retrofit into an existing space or for ceiling mount or wall mount installation (UL listed for both) into your next multifamily or single-family project. BreezSlim breaks the mold of the everyday bathroom exhaust fan. Available in contractor packs.

Features:

Innovative brushless DC motor design for long life, low noise and low power consumption.

- Energy savings up to 85%¹ and 3" duct (standard)
- 1 sone – The quietest ever in a 7 1/2" x 7 1/4" bath fan
- Exceeds ENERGY STAR requirements by 217% in energy efficiency²
- UL listed for both ceiling-mount and wall-mount installation

1. Based upon SLM50 vs. market AC motor

2. Based upon ENERGY STAR v4.0 criteria for residential ventilating fans

	Delta Breez	Market AC Motor
Energy Use (Watts)	6.4	45.2
Noise Level (Sones)	1.0	4.0
Annual Energy Cost per Fan (24/7) ³	\$6.73	\$47.56


3. Calculations based upon U.S. average retail electricity. Actual results may vary




Available with
Project Pack Components



Available with
metal duct adapter



Fan Housing



Fan Grille



LED Indicator Light:
SLM50, SLM70



LED Indicator Light:
SLM70D



LED Indicator Light:
SLM70H






Delta BreezSlim Series (3" duct)



SLM70ELED



Specifications

SLM50* - 50 CFM Single Speed Exhaust Fan



3" Duct (Standard)		
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	50	36
Sones	1.0	1.2
Power Consumption (Watts)	6.4	6.3
Energy Efficiency (CFM/Watts)	11.6	7.4
Current (Amps)	0.18 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available SLM-A (housing) and SLM50-B (motor grille)		

SLM70 - 70 CFM Single Speed Exhaust Fan

3" Duct (Standard)		
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	70	54
Sones	2.0	1.5
Power Consumption (Watts)	13.2	11.6
Energy Efficiency (CFM/Watts)	5.8	5.0
Current (Amps)	0.29 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available SLM-A (housing) and SLM70-B (motor grille)		

SLM70H - 70 CFM Fan with Humidity sensor



	3" Duct (Standard)	
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	70	54
Sones	2.0	1.5
Power Consumption (Watts)	13.2	11.6
Energy Efficiency (CFM/Watts)	5.8	5.0
Current (Amps)	0.29 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available SLM-A (housing) and SLM70H-B (motor grille)		

SLM70D - 70 CFM Fan with Dual Speed

	Continuous low speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	40	25	70	50
Sones	0.8	1.0	2.0	1.5
Power Consumption (Watts)	5.0	6.0	13.2	11.6
Energy Efficiency (CFM/Watts)	12.9	6.3	7.1	6.2
Current (Amps)	0.29 Max			
Power Rating (V/Hz)	120/60			

SLM70ELED - 70 CFM Fan with Edge-Lit Dimmable LED Light


3" Duct (Standard)		
Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	70	53
Sones	2.0	1.5
Power Consumption (Watts)	13.2	11.6
Energy Efficiency (CFM/Watts)	6.0	5.4
Current (Amps)	0.29 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watts)	13.0	

Delta BreezSignature SLM-DGL Designer Grille

The SLM-DGL designer fan grille is offered as an alternative to the standard grille on Delta Breez SLM50, SLM70, SLM70H, ITG50, ITG80, ITG70BT, ITG80H, and ITG100.

Features:

- Adds modern aesthetic to bathroom
- Made of long-lasting ABS material
- Paintable to coordinate with any style bathroom
- Size: 10 3/4" x 10 3/4"



* Product is ENERGY STAR Most Efficient 2021 distinction and ENERGY STAR qualified




Delta BreezProfessional (6" duct)

Large space solution.

Single speed 200 or 300 CFM. Quiet operation from 1 to 2 sones. For spaces 200-300 sq. ft. Perfect for large bathrooms, laundry rooms, conference rooms. UL approved for ceiling mount only.

Features:

- DC motor technology, energy saving up to 60%¹
- Galvanized steel body
- Detachable 6" diameter metal duct adapter
- Built-in backdraft damper
- LED indicator light green when power is on



	Delta Breez	Market AC Motor
Energy Use (Watts)	17.5	57
Noise Level (Sones)	1.0	1.2
Annual Energy Cost per Fan (24/7) ²	\$18.40	\$58.59

1. Based upon Breez Pro200 vs. Market AC motor

2. Calculations based upon U.S. average retail electricity. Actual results may vary

Specifications

Pro200* - 200 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	200	163
Sones	1.0	1.3
Power Consumption (Watts)	17.5	21.5
Energy Efficiency (CFM/Watts)	11.4	7.5
Current (Amps)	0.52 Max	
Power Rating (V/Hz)	120/60	

Pro300 - 300 CFM Fan

Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	300	268
Sones	2.0	2.5
Power Consumption (Watts)	41	43
Energy Efficiency (CFM/Watts)	7.3	6.2
Current (Amps)	0.72 Max	
Power Rating (V/Hz)	120/60	

* Product is ENERGY STAR Most Efficient 2021 distinction and ENERGY STAR qualified



4 Inch Duct Series

Builder's best solution

Delta BreezGreenBuilder ventilation fans were designed with green builders and contractors in mind. High speed 80 CFM or 100 CFM. For spaces 80-100 sq. ft. Quiet operation from 0.8 to 1.4 sones. Options include adjustable low speed, dimmable LED light, and decorative dimmable LED light, motion and/or humidity sensor. Ceiling Radiation Damper and designer grille available separately. Fans only and fans with humidity sensor are UL listed for ceiling and wall mount; fans/LED light are UL listed for ceiling mount only.

Features:

Innovative brushless DC motor design for long life, low noise and low power consumption

- Energy savings up to 61%¹ and 4" duct (standard)
- Lowest sone level rated by HVI as low as 0.8 sones
- Power consumption down to 10.5 Watts
- Exceeds ENERGY STAR requirements by 192% in energy efficiency²
- Fan and Fan/dimmable LED Light combination project pack available
- Fan only models are UL listed for both ceiling-mount and wall-mount installation

Fan/Dimmable LED Light:

- 13-Watt Dimmable LED light included (dimmer switch not included). It is equivalent to a 60-Watt incandescent bulb
- Main light output of 850 lumens, 3000K and 90 CRI

Fan/Dimmable LED Light DECOR:

- 13-Watt Dimmable LED light included (dimmer switch not included)
- Main light output of 950 Lumens, 3000K and 80 CRI
- Beautifully designed ventilation fan with frosted glass globe and dimmable LED light allows for quiet ventilation
- 4-decorative fans in one; includes chrome, brushed nickel, brushed bronze, and polished white finials to match any décor

1. Based on GreenBuilder GBR80 vs. market AC motor fan

2. Based upon GBR80CFM vs. ENERGY STAR v4.0 criteria for residential ventilating fans




Fan Only



Fan/Dimmable LED Light




GBR100LED-DECOR



Project Pack Components Available



BreezGreenBuilder Series Dimensions



LED Indicator Light:
GBR80, GBR80LED,
GBR100, GBR100LED
Fan is running




LED Indicator Light:
GBR80HLED, GBR80MHLED, GBR80H,
GBR100H, GBR100HLED
Humidity Sensing Full Speed




Built-in Controls

GBR80H, GBR80HLED,
GBR80MHLED



Built-in Controls

GBR100H,
GBR100HLED



Specifications

GBR80 - 80 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	64
Sones	0.8	1.5
Power Consumption (Watts)	10.5	12.5
Energy Efficiency (CFM/Watts)	7.6	5.1
Current (Amps)	0.21 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available GBR-A (housing) and GBR80-B (motor/grille)		

GBR80H - 80 CFM Fan with Humidity Sensor



Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	35	80	64
Sones	<0.3	1.0	0.8	1.5
Power Consumption (Watts)	4.0	6.0	9.7	11.8
Energy Efficiency (CFM/Watts)	12.5	5.8	8.2	5.4
Current (Amps)	0.22 Max			
Power Rating (V/Hz)	120/60			

GBR80HLED - 80 CFM

Fan/Dimmable LED Light with Humidity Sensor



Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	33	80	63
Sones	<0.3	0.8	0.8	1.5
Power Consumption (Watts)	4.4	6.0	11	13
Energy Efficiency (CFM/Watts)	11.3	5.5	7.2	4.8
Current (Amps)	0.33 Max			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			

GBR80LED - 80 CFM Fan/Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	63
Sones	0.8	1.5
Power Consumption (Watts)	11	13
Energy Efficiency (CFM/Watts)	7.2	4.8
Current (Amps)	0.33 Max	
Power Rating (V/Hz)	120/60	
Dimmable LED Light (Watts)	13	



Delta BreezGreenBuilder Series (4" duct)

Specifications

GBR80MHLED - 80 CFM



Fan/Dimmable LED Light w/Humidity & Motion Sensor

Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	33	80	63
Sones	<0.3	0.8	0.8	1.5
Power Consumption (Watts)	4.4	6.0	11	13
Energy Efficiency (CFM/Watts)	11.3	5.5	7.2	4.8
Current (Amps)	0.33 Max			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			

GBR100 - 100 CFM Single Speed Exhaust Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	77
Sones	1.4	1.5
Power Consumption (Watts)	12.6	13.5
Energy Efficiency (CFM/Watts)	7.9	5.7
Current (Amps)	0.22 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available GBR-A (housing) and GBR100-B (motor/grille)		

GBR100H - 100 CFM Fan with Humidity Sensor



Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	60	42	100	77
Sones	0.5	0.7	1.4	1.5
Power Consumption (Watts)	4.9	6.3	12.6	13.5
Energy Efficiency (CFM/Watts)	12.2	6.6	7.9	5.7
Current (Amps)	0.24 Max			
Power Rating (V/Hz)	120/60			

GBR100HLED - 100 CFM



Fan/Dimmable LED Light with Humidity Sensor

Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	60	42	100	72
Sones	0.6	1.0	1.5	1.5
Power Consumption (Watts)	4.8	6.2	13.6	11.6
Energy Efficiency (CFM/Watts)	12.5	6.7	7.3	6.2
Current (Amps)	0.35 Max			
Power Rating (V/Hz)	120/60			
Dimmable LED Light (Watts)	13			

GBR100LED - 100 CFM Fan/Dimmable LED Light




Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	72
Sones	1.5	1.5
Power Consumption (Watts)	13.6	11.6
Energy Efficiency (CFM/Watts)	7.3	6.2
Current (Amps)	0.35 Max	
Power Rating (V/Hz)	120/60	
Dimmable LED Light (Watts)	13	

GBR100LED-DECOR - 100 CFM



Fan/Dimmable LED Light Decor

Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	72
Sones	1.5	2.0
Power Consumption (Watts)	13	12.5
Energy Efficiency (CFM/Watts)	7.6	5.7
Current (Amps)	0.32 Max	
Power Rating (V/Hz)	120/60	
Dimmable LED Light (Watts)	13	




1. Calculations based upon U.S. average retail electricity. Actual results may vary

Delta BreezGreenBuilder GBR-DGL Designer Grille

The GBR-DGL designer fan grille is offered as an alternative to the standard grille on GBR80, GBR80H, GBR100, and GBR100H.

Features:

- Adds modern aesthetics to the bathroom
- Made of long-lasting ABS material
- Paintable to coordinate with any style bathroom
- Size: 10 $\frac{3}{4}$ " x 10 $\frac{3}{4}$ "





Delta BreezGreenBuilder GBR-CRD Ceiling Radiation Damper

The damper employs a folded curtain style blade for point-of-origin control of radiant heat in a ventilation system. GBR-CRD installs in the ceiling membrane for floor/ceiling or roof/ceiling assemblies with a fire resistance rating up to and including 3 hours.

Features:

- UL and cUL listed and exceeds UL 555C for use in 3-hour fire rated assemblies
- Warnock-Hersey certified for use in fire rated floor/ceiling or roof/ceiling assemblies
- CSFM listing: 3226-0368:104
- Meets NFPA Standards: 90A and 101
- Meets Building Code Standards: IBC, NBC, NFPA, SBC and UBC

- Available for Delta Breez Ventilation Fans: GBR80, GBR80H, GBR80HLED, GBR80LED, GBR80MHLED, GBR100, GBR100H, GBR100HLED and GBR100LED





4 Inch Duct Series

Economical ventilation solution

Single speed 50, 80, or 100 CFM. For spaces 50-100 sq. ft. Quiet operation from 0.7 to 1.5 sones. Options include dimmable LED light or edge-lit dimmable LED light, adjustable humidity sensor, Bluetooth® speaker. Ceiling Radiation Damper and designer grille available separately. Fans only and fan with humidity sensor are UL listed for ceiling and wall mount; fans/dimmable LED light are UL listed for ceiling mount only.

Features:

Innovative brushless DC motor design for long life, low noise and low power consumption

- Power rating of 120 volts/60Hz
- Brushless DC motor engineered to run continuously
- Motor equipped with thermal cutoff fuse
- Removable with permanently lubricated plug-in motor
- Built-in soft start function to increase bearings' life
- Automatically powers off when impeller is locked abnormally

Fan/Dimmable LED Light:

- 13-Watt LED light included (equivalent to a 60-Watt incandescent bulb)
- Main light output of 850 lumens, 3000K and 90 CRI
- Dimmable LED light (dimmer switch not included)

Fan/Edge-lit Dimmable LED Light:

- 13-Watt LED light
- Main light output of 1000 lumens, 3000K, and 80 CRI
- Dimmable LED light (dimmer switch not included)
- 13-Watt integrated dimmable edge-lit LED light lasts up to 30,000 hours

Bluetooth® Speaker:

- Bluetooth® 3.0, speaker 3W and 4 Ohm
- Play audio through most Bluetooth® wireless devices

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by Delta Electronics, Inc. is under license. Other trademarks and trade names are those of their respective owners.



Fan Only



Fan with Bluetooth® speaker




Fan/Dimmable LED light






Fan/Edge-lit
Dimmable LED light



Grille for Fan/LED Light





Fan/LED Edge-Lit Dimmable LED light,
Flat Round Panel




Grille for Fan with Bluetooth® Speaker


BreezIntegrity Series Dimensions



Grille for Fan Only



Grille for Fan/Edge-lit LED Light



Grille for Fan/Edge-lit LED Light
Flat Round Panel




Built-in Controls

ITG50HLED



ITG80H



LED Indicator Light: ITG80H, ITG50HLED

Humidity Sensing

Full Speed



Project Pack
Components
Available

Specifications

ITG50* - 50 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	50	37
Sones	0.7	1.3
Power Consumption (Watts)	5	7
Energy Efficiency (CFM/Watts)	12.5	6.7
Current (Amps)	0.14 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available ITG-A (housing) and ITG50-B (motor grille)		

ITG50LED* - 50 CFM Fan/Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	50	38
Sones	0.7	1.3
Power Consumption (Watts)	5	7
Energy Efficiency (CFM/Watts)	11	6.5
Current (Amps)	0.22 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watts)	13	

ITG50HLED* - 50 CFM Fan / Dimmable LED Light w/ Humidity Sensor



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	50	38
Sones	0.7	1.3
Power Consumption (Watts)	5	7
Energy Efficiency (CFM/Watts)	11	6.5
Current (Amps)	0.22 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watts)	13	

ITG70BT* - 70 CFM Fan with Bluetooth® Speaker



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	70	59
Sones	1.0	1.5
Power Consumption (Watts)	6.6	8.3
Energy Efficiency (CFM/Watts)	10.7	7.2
Current (Amps)	0.2 Max	
Power Rating (V/Hz)	120/60	

ITG80 - 80 CFM Fan

Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	60
Sones	1.3	1.4
Power Consumption (Watts)	10	12
Energy Efficiency (CFM/Watts)	8.4	6.6
Current (Amps)	0.20 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available ITG-A (housing) and ITG80-B (motor grille)		

* Product is ENERGY STAR Most Efficient 2021 distinction and ENERGY STAR qualified

ITG80H - 80 CFM Fan with Humidity Sensor



Fan Speed	Continuous Low Speed		Full Speed	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	36	80	60
Sones	0.7	1.0	1.5	1.5
Power Consumption (Watts)	5.0	7.0	10	11
Energy Efficiency (CFM/Watts)	12.0	6.9	9.0	6.2
Current (Amps)	0.20 Max			
Power Rating (V/Hz)	120/60			

ITG80LED - 80 CFM Fan/Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	60
Sones	1.3	1.3
Power Consumption (Watts)	11.3	11.5
Energy Efficiency (CFM/Watts)	7.2	6.2
Current (Amps)	0.14 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watt)	13	

ITG100 - 100 CFM Fan



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	85
Sones	1.5	2.0
Power Consumption (Watts)	17	21
Energy Efficiency (CFM/Watts)	7.6	5.3
Current (Amps)	0.33 Max	
Power Rating (V/Hz)	120/60	
Project Pack Components Available ITG-A2 (housing) and ITG100-B (motor grille)		

ITG100ELED - 100 CFM Fan/ Edge-lit Dimmable LED Light



Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	85
Sones	1.5	2.0
Power Consumption (Watts)	17	21
Energy Efficiency (CFM/Watts)	7.5	5.9
Current (Amps)	0.47 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watt)	13	

ITG100RLED - 100 CFM Fan/ Edge-lit Dimmable LED Light, Flat Round Panel




Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	100	85
Sones	1.5	2.0
Power Consumption (Watts)	17	21
Energy Efficiency (CFM/Watts)	7.5	5.9
Current (Amps)	0.47 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watt)	13	

Delta BreezIntegrity ITG-CRD Ceiling Radiation Damper

The damper employs a folded curtain style blade for Point-of-origin control of radiant heat in a ventilation system. ITG-CRD installs in the ceiling membrane for floor/ceiling or roof/ceiling assemblies with a fire resistance rating up to and including 3 hours.

Features:

- UL and cUL listed and exceeds UL 555C for use in 3-hour fire rated assemblies
- Warnock-Hersey certified for use in fire rated floor/ceiling or roof/ceiling assemblies
- Available for use with Delta Breez ventilation fans ITG100, ITG80, ITG50, ITG80H, ITG80LED, and ITG50LED.





4 Inch Duct Series

Fan/heater solution to warm and delight.

Quiet operation from 0.7 to 1.5 sones. 80 or 110 CFM for spaces 80-110 sq. ft. Options include dimmable LED or fan/heater only. Built-in thermostat to regulate room temperature for maximum comfort. UL approved for ceiling mount only. Not UL approved for mounting over bathtub or shower.

Features:


- Energy saving DC motor technology
- Built-in thermostat for consistent temperature
- Metal guard to prevent user contact with heating element
- Heater module equipped with thermal cut off fuse
- Duct diameter of 4"
- 1300/1600 Watts heating element evaluated by cUL for safety standards

Fan/LED Light:

- 13-Watt LED lamp included (equivalent to a 60-Watt incandescent bulb)
- Main light output of 850 lumens, 3000K and 90 CRI
- Dimmable LED Light (dimmer switch not included)





Built-in thermostat



¹. Calculations based upon U.S. average retail electricity. Actual results may vary



RAD80 Fan with Heater



Specifications


RAD80 - 80 CFM Fan with Heater




Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	54
Sones	1.5	NA
Power Consumption (Watts)	11.7	8.2
Energy Efficiency (CFM/Watts)	7.0	6.6
Current (Amps)	11	
Power Rating (V/Hz)	120/60	
Heating element (Watts)	1300	
Total power (Watts)	1314	



RAD80LED Fan/Dimmable LED Light/Heater



RAD110LED Fan/Dimmable LED Light/Heater



RAD80LED - 80 CFM Fan/Dimmable LED Light w/ Heater LED

Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	54
Sones	1.5	N/A
Power Consumption (Watts)	11.7	8.2
Energy Efficiency (CFM/Watts)	7.0	6.6
Current (Amps)	11	
Power Rating (V/Hz)	120/60	
Heating element (Watts)	1300	
Lamp (Watts)	13	
Total power (Watts)	1327	

RAD110LED - 110 CFM Fan/Dimmable LED Light w/ Heater LED

Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	110	85
Sones	0.7	1.0
Power Consumption (Watts)	12.0	13.0
Energy Efficiency (CFM/Watts)	11	7.8
Current (Amps)	14	
Power Rating (V/Hz)	120/60	
Heating element (Watts)	1600	
Lamp (Watts)	13	
Total power (Watts)	1650	



Delta BreezRecessed (4" duct)

Fan design solution.



80 CFM fan disguised as a recessed light with Dimmable LED. For 80 sq. ft. space. Quiet operation at 1.5 sones. UL approved for ceiling mount only.

Features:

- ENERGY STAR qualified
- Brushless DC motor lasts 70,000 hours for extended reliability
- Quiet Operation at 1.5 sones

Fan/Dimmable LED Light:

- 13-Watt Dimmable LED light included (dimmer switch not included)
- LED main light output 850 lumens, 3000K, and 90 CRI



	Delta Breez	Market AC Motor
Energy Use (Watts)	14.5	34.4
Noise Level (Sones)	1.5	1.5
Annual Energy Cost per Fan (24/7) ¹	\$15.25	\$35.91

¹ Calculations based upon U.S. average retail electricity. Actual results may vary

Specifications


REC80LED - 80 CFM Fan/Dimmable LED Light




Static Pressure (Inches w.g.)	0.1	0.25
Air Flow (CFM)	80	65
Sones	1.5	2.0
Power Consumption (Watts)	14.5	14.5
Energy Efficiency (CFM/Watts)	6.1	5.4
Current (Amps)	0.34 Max	
Power Rating (V/Hz)	120/60	
LED Light (Watts)	13	

BreezSignature Fan Curves


SIG80-110D Fan Curve




SIG80-110HLED Fan Curve



SIG80-110MHLED Fan Curve




SIG110 Fan Curve




BreezSignature Fan Curves

VFB25ADBT Fan Curve




BreezElite Fan Curves


ELT80-110 Fan Curve




ELT80-110LED Fan Curve



ELT80-110D / ELT80-110H ELT80-110MH Fan Curve




ELT80-110DLED / ELT80-110HLED ELT80-110MHLED Fan Curve




BreezSmart Fan Curves


SMT130 Fan Curve




SMT130H & SMT130M Fan Curve




SMT150 Fan Curve



SMT150D Fan Curve




SMT150LED Fan Curve




BreezGreenBuilder Fan Curves


GBR80 Fan Curve




GBR80H Fan Curve




GBR80HLED Fan Curve




GBR80LED Fan Curve




GBR100 Fan Curve




GBR100H Fan Curve




GBR100HLED Fan Curve



GBR100LED Fan Curve




GBR100LED-DECOR Fan Curve




BreezSlim Fan Curves


**SLM80-110 & SLM80-110LED
SLM80-110-C & SLM80-110LED-C**



**SLM80-110D & SLM80-110DLED
SLM80-110D-C & SLM80-110DLED-C**




SLM50 Fan Curve




BreezSlim Fan Curves


SLM70 Fan Curve




SLM70H Fan Curve




SLM70D Fan Curve




SLM70ELED Fan Curve



SLM80 Fan Curve




SLM100 Fan Curve




BreezIntegrity Fan Curves


ITG50 Fan Curve




ITG50LED Fan Curve




ITG70BT Fan Curve




ITG80 Fan Curve



ITG80H Fan Curve




ITG80LED Fan Curve




BreezIntegrity Fan Curves


ITG100 Fan Curve



ITG100ELED Fan Curve




ITG100RLED Fan Curve




BreezRecessed Fan Curves


REC80LED Fan Curve



Pro200 Fan Curve




Pro300 Fan Curve




BreezRadiance Fan Curve


RAD80 & RAD80-DGL Fan Curve

























RAD80LED & RAD80ELED Fan Curve







RAD110LED Fan Curve































PRODUCT SELECTION GUIDE: FIND THE MOST SUITABLE FAN

	Model #	Air Flow (CFM)	Duct Size	Description	
Signature	SIG80-110	80-110	6 inches	Single Speed	
	SIG80-110LED	80-110	6 inches	Fan/Dimmable LED Light/Night-Light	
	SIG80-110ELED	80-110	6 inches	Fan/Edge-lit Dimmable LED Light w/ adjustable color temperature	
	SIG80-110D	80-110	6 inches	Fan with Dual Speed	
	SIG80-110DLED	80-110	6 inches	Fan/Dimmable LED Light/Night-Light w/Dual Speed	
	SIG80-110H	80-110	6 inches	Fan with Humidity Sensor	
	SIG80-110HLED	80-110	6 inches	Fan/Dimmable LED Light/Night-Light w/ Humidity Sensor	
	SIG80-110MH	80-110	6 inches	Fan with Motion & Humidity Sensor	
	SIG80-110MHLED	80-110	6 inches	Fan/ Dimmable LED Light/Night-Light with Motion & Humidity Sensor	
	SIG80	80	4 inches	Single Speed	
	SIG80D	80	4 inches	Fan with Dual Speed	
	SIG110	110	4 inches	Single Speed	
	VFB25ADB	110	4 inches	Fan with Bluetooth®	
Smart	SMT130	130	6 inches	Single Speed	
	SMT130M	130	6 inches	Fan with Motion Sensor	
	SMT130H	130	6 inches	Fan with Humidity Sensor	
	SMT150	150	6 inches	Single Speed	
	SMT150D	150	6 inches	Fan with Dual Speed	
	SMT150LED	150	6 inches	Fan/ Dimmable LED Light / Night-Light	
	SMT150-200	150-200	6 inches	Single Speed	
	SMT150-200LED	150-200	6 inches	Fan/ Dimmable LED Light	
Recessed	REC80LED	80	4 inches	Fan/Dimmable LED Light	
Elite	ELT80-110	80-110	6 inches	Single Speed	
	ELT80-110LED	80-110	6 inches	Fan/Dimmable LED Light	
	ELT80-110D	80-110	6 inches	Fan with Dual Speed	
	ELT80-110DLED	80-110	6 inches	Fan/Dimmable LED Light with Dual Speed	
	ELT80-110H	80-110	6 inches	Fan with Humidity Sensor	
	ELT80-110HLED	80-110	6 inches	Fan/Dimmable LED Light with Humidity Sensor	
	ELT80-110MH	80-110	6 inches	Fan with Motion and Humidity Sensor	
	ELT80-110MHLED	80-110	6 inches	Fan/Dimmable LED Light w/ Motion and Humidity Sensor	





 LED Light
  Dimmable LED Light
  Adjustable motion sensor
  Adjustable humidity sensor
  Adjustable dual speed

Motor	Noise (Sones)	Energy Use (Watts)	Energy Efficiency (CFM/Watts)	Electric Bill ¹		 Most Efficient 2021 www.energystar.gov	 Intermittent	 Continuous
DC	<0.3	6.2	15.4	\$6.52	Y	Y	Y	Y
DC	<0.3	6.8 (Fan Only)	13.8	\$7.15	Y	Y	Y	Y
DC	<0.3	7.5 (Fan Only)	11.7	\$7.89	Y	Y	Y	Y
DC	<0.3	6.2	15.4	\$6.50	Y	Y	Y	Y
DC	<0.3	6.8 (Fan Only)	13.8	\$7.20	Y	Y	Y	Y
DC	<0.3	6.2	15.4	\$6.50	Y	Y	Y	Y
DC	<0.3	6.8 (Fan Only)	13.8	\$7.20	Y	Y	Y	Y
DC	<0.3	6.2	15.4	\$6.50	Y	Y	Y	Y
DC	<0.3	6.8 (Fan Only)	13.8	\$7.20	Y	Y	Y	Y
DC	<0.3	8.7	9.7	\$9.15	Y		Y	Y
DC	<0.3	8.7	9.7	\$9.15	Y		Y	Y
DC	<0.3	13.6	9.0	\$14.31	Y		Y	Y
DC	1.0	14.2	7.7	\$14.94	Y		Y	Y
DC	<0.3	11.6	11.2	\$12.10	Y	Y	Y	Y
DC	<0.3	11.6	11.2	\$12.10	Y	Y	Y	Y
DC	<0.3	11.6	11.2	\$12.10	Y	Y	Y	Y
DC	<0.3	16.9	8.8	\$17.63	Y		Y	Y
DC	<0.3	16.9	8.8	\$17.63	Y		Y	Y
DC	0.5	17.6 (Fan Only)	8.5	\$18.51	Y		Y	Y
DC	0.5	14.0	10.7	\$14.71	Y		Y	Y
DC	0.5	15.0 (Fan Only)	10.0	\$15.77	Y		Y	Y
DC	1.5	14.5 (Fan only)	6.1	\$15.25	Y		Y	
DC	0.5	7.0	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0 (Fan Only)	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0 (Fan Only)	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0 (Fan Only)	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0	11.4	\$7.36	Y	Y	Y	Y
DC	0.5	7.0 (Fan Only)	11.4	\$7.36	Y	Y	Y	Y

PRODUCT SELECTION GUIDE: FIND THE MOST SUITABLE FAN (cont.)

	Model #	Air Flow (CFM)	Duct Size	Description	
GreenBuilder	GBR80	80	4 inches	Single Speed	
	GBR80H	80	4 inches	Fan with Humidity Sensor	
	GBR80HLED	80	4 inches	Fan/Dimmable LED Light with Humidity Sensor	
	GBR80LED	80	4 inches	Fan/Dimmable LED Light	
	GBR80MHLED	80	4 inches	Fan/ Dimmable LED Light w/Humidity & Motion Sensor	
	GBR100	100	4 inches	Single Speed	
	GBR100H	100	4 inches	Fan with Humidity Sensor	
	GBR100HLED	100	4 inches	Fan/Dimmable LED Light with Humidity Sensor	
	GBR100LED	100	4 inches	Fan/Dimmable LED Light	
	GBR100LED-DECOR	100	4 inches	Fan/Dimmable LED Light Decor	
Slim	SLM50	50	3 inches	Single Speed	
	SLM70	70	3 inches	Single Speed	
	SLM70ELED	70	3 inches	Fan with Edge-Lit Dimmable LED Light	
	SLM70H	70	3 inches	Fan with Humidity Sensor	
	SLM70D	70	3 inches	Fan with Dual Speed	
	SLM80	80	4 inches Oval	Single Speed	
	SLM100	100	4 inches Oval	Single Speed	
	SLM80-110	80-110	4 inches Oval	Single Speed	
	SLM80-110D	80-110	4 inches Oval	Fan with Dual Speed	
	SLM80-110LED	80-110	4 inches Oval	Fan/Dimmable LED Light	
	SLM80-110DLED	80-110	4 inches Oval	Fan/Dimmable LED Light with Dual Speed	
	SLM80-110-C	80-110	4 inches Oval	Single Speed	
	SLM80-110D-C	80-110	4 inches Oval	Fan with Dual Speed	
	SLM80-110LED-C	80-110	4 inches Oval	Fan/Dimmable LED Light	
	SLM80-110DLED-C	80-110	4 inches Oval	Fan/Dimmable LED Light with Dual Speed	
Integrity	ITG50	50	4 inches	Single Speed	
	ITG50LED	50	4 inches	Fan/Dimmable LED Light	
	ITG70BT	70	4 inches	Fan with Bluetooth®	
	ITG80	80	4 inches	Single Speed	
	ITG80H	80	4 inches	Fan with humidity Sensor	
	ITG80LED	80	4 inches	Fan/Dimmable LED Light	
	ITG100	100	4 inches	Single Speed	
	ITG100ELED	100	4 inches	Fan/Edge-lit Dimmable LED Light	
	ITG100RLED	100	4 inches	Fan/Edge-Lit Dimmable LED Light, Flat Round Panel	
Radiance	RAD80	80	4 inches	Fan with Heater	
	RAD80-DGL	80	4 inches	Fan/Designer Grille with Heater	
	RAD80LED	80	4 inches	Fan/Dimmable LED Light with Heater	
	RAD80ELED	80	4 inches	Fan/Dimmable Edge-lit LED Light with Heater	
	RAD110LED	110	4 inches	Fan/Dimmable LED Light with Heater	
Professional	Pro200	200	6 inches	Single Speed	
	Pro300	300	6 inches	Single Speed	

 LED Light
  Dimmable LED Light
  Adjustable motion sensor
  Adjustable humidity sensor
  Adjustable dual speed

Motor	Noise (Sones)	Energy Use (Watts)	Energy Efficiency (CFM/Watts)	Electric Bill ¹		 Most Efficient 2021 www.energystar.gov	 Intermittent	 Continuous
DC	0.8	10.5	7.6	\$10.95	Y		Y	Y
DC	0.8	9.7	8.2	\$10.20	Y		Y	Y
DC	0.8	11.0 (Fan only)	7.2	\$11.57	Y		Y	Y
DC	0.8	11.0 (Fan only)	7.2	\$11.57	Y		Y	Y
DC	0.8	11.0 (Fan only)	7.2	\$11.57	Y		Y	Y
DC	1.4	12.6	7.9	\$13.15	Y		Y	
DC	1.4	12.6	7.9	\$13.15	Y		Y	
DC	1.5	13.6 (Fan only)	7.3	\$14.31	Y		Y	
DC	1.5	13.6 (Fan only)	7.3	\$14.31	Y		Y	
DC	1.5	13.0 (Fan only)	7.6	\$13.68	Y		Y	
DC	1.0	6.4	11.6	\$6.73	Y	Y		Y
DC	2.0	13.2	5.8	\$13.88	Y		Y	
DC	2.0	13.2 (Fan Only)	6.0	\$13.88	Y		Y	Y
DC	2.0	13.2	5.8	\$13.88	Y		Y	
DC	2.0	13.2	7.1	\$13.88	Y		Y	Y
DC	0.7	8.5	9.4	\$8.94	Y		Y	Y
DC	1.0	14.5	6.8	\$15.25	Y		Y	Y
DC	0.4	8.5	9.4	\$8.94	Y		Y	Y
DC	0.4	8.5	9.4	\$8.94	Y		Y	Y
DC	0.4	9.0 (Fan Only)	8.8	\$9.47	Y		Y	Y
DC	0.4	9.0 (Fan Only)	8.8	\$9.47	Y		Y	Y
DC	0.4	8.5	9.4	\$8.94	Y		Y	Y
DC	0.4	8.5	9.4	\$8.94	Y		Y	Y
DC	0.4	9.0 (Fan Only)	8.8	\$9.47	Y		Y	Y
DC	0.4	9.0 (Fan Only)	8.8	\$9.47	Y		Y	Y
DC	0.7	5.0	12.5	\$5.26	Y	Y		Y
DC	0.7	5.0 (Fan Only)	12.5	\$5.26	Y	Y		Y
DC	1.0	8.4	10.6	\$8.83	Y	Y	Y	Y
DC	1.3	9.5	8.4	\$9.98	Y		Y	
DC	1.5	10.0	9.0	\$10.51	Y		Y	Y
DC	1.3	11.3 (Fan Only)	7.2	\$11.88	Y		Y	
DC	1.5	17.0	7.6	\$17.88	Y		Y	
DC	1.5	17.0 (Fan Only)	7.5	\$17.88	Y		Y	
DC	1.5	17.0 (Fan Only)	7.5	\$17.88	Y		Y	
DC	1.5	11.7	7.0	\$12.31			Y	
DC	1.5	14.5	5.5	\$15.25			Y	
DC	1.5	11.7 (Fan Only)	7.0	\$12.31			Y	
DC	1.5	14.5 (Fan Only)	5.5	\$15.25			Y	
DC	0.7	12.0 (Fan Only)	11	\$12.62			Y	Y
DC	1.0	17.5	11.4	\$18.39	Y	Y	Y	Y
DC	2.0	41	7.3	\$43.09	Y		Y	

EQUIVALENT DUCT LENGTHS

This chart shows Equivalent Duct Lengths (EDL) for BreezSignature, BreezSlim, BreezGreenBuilder, BreezSmart, BreezRadiance, BreezProfessional, BreezIntegrity and BreezRecessed models by CFM (airflow) output for duct lengths from 40ft to 100ft.

	Breez Models	Mode(s)	Duct Size	40ft	60ft	80ft	100ft
Signature	SIG80-110 (80-110 CFM)	Single Speed	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110LED (80-110 CFM)	Fan/ Dimmable LED Light/Night-Light	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110ELED (80-110 CFM)	Fan/Edge-lit Dimmable LED Light w/ adjustable color temperature	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110D (80-110 CFM)	Fan with Dual Speed	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110DLED (80-110 CFM)	Fan/ Dimmable LED Light/Night-Light with Dual Speed	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110H (80-110 CFM)	Fan with Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110HLED (80-110 CFM)	Fan/Dimmable LED Light/Night-Light w/ Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110MH (80-110 CFM)	Fan with Motion & Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80-110MHLED (80-110 CFM)	Fan/ Dimmable LED Light/Night-Light w/ Motion and Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	110 CFM
	SIG80 (80 CFM)	Single Speed	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	SIG80D (80 CFM)	Fan with Dual Speed	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	SIG110 (110 CFM)	Single Speed	4 inches	90 CFM	90 CFM	80 CFM	80 CFM
	VFB25ADBT (110 CFM)	Fan with Bluetooth®	4 inches	90 CFM	80 CFM	70 CFM	70 CFM
Smart	SMT130 (130 CFM)	Single Speed	6 inches	130 CFM	130 CFM	120 CFM	120 CFM
	SMT130H (130 CFM)	Multi-Speed with Humidity Sensor	6 inches	130 CFM	130 CFM	120 CFM	120 CFM
	SMT130M (130 CFM)	Multi-Speed with Motion Sensor	6 inches	130 CFM	130 CFM	120 CFM	120 CFM
	SMT150 (150 CFM)	Single Speed	6 inches	150 CFM	150 CFM	140 CFM	140 CFM
	SMT150D (150 CFM)	Dual Speed	6 inches	150 CFM	150 CFM	140 CFM	140 CFM
	SMT150LED (150 CFM)	Fan/Dimmable LED Light / Night-Light	6 inches	150 CFM	150 CFM	150 CFM	150 CFM
Recessed	REC80LED (80 CFM)	Fan/Dimmable LED Light	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
Elite	ELT80-110 (80-110 CFM)	Single Speed	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110LED (80-110 CFM)	Fan/Dimmable LED Light	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110D (80-110 CFM)	Fan with Dual Speed	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110DLED (80-110 CFM)	Fan/Dimmable LED Light with Dual Speed	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110H (80-110 CFM)	Fan with Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110HLED (80-110 CFM)	Fan/Dimmable LED Light w/ Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110MH (80-110 CFM)	Fan with Motion and Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
	ELT80-110MHLED (80-110 CFM)	Fan/Dimmable LED Light w/ Motion and Humidity Sensor	6 inches	110 CFM	110 CFM	110 CFM	100 CFM
GreenBuilder	GBR80 (80 CFM)	Single Speed	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	GBR80H (80 CFM)	Fan with Humidity Sensor	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	GBR80HLED (80 CFM)	Fan/Dimmable LED Light w/ Humidity Sensor	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	GBR80LED (80 CFM)	Fan/Dimmable LED Light	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	GBR80MHLED (80 CFM)	Fan/Dimmable LED Light with Humidity & Motion Sensor	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	GBR100 (100 CFM)	Single Speed	4 inches	80 CFM	70 CFM	70 CFM	60 CFM
	GBR100H (100 CFM)	Fan with Humidity Sensor	4 inches	80 CFM	70 CFM	70 CFM	60 CFM
	GBR100HLED (100 CFM)	Fan/Dimmable LED Light w/Humidity Sensor	4 inches	80 CFM	70 CFM	70 CFM	60 CFM
	GBR100LED (100 CFM)	Fan/ Dimmable LED Light	4 inches	80 CFM	70 CFM	70 CFM	60 CFM
	GBR100LED-DECOR (100 CFM)	Fan/ Dimmable LED Light Decor	4 inches	80 CFM	70 CFM	60 CFM	60 CFM

EQUIVALENT DUCT LENGTHS (cont.)

	Breez Models	Mode(s)	Duct Size	40ft	60ft	80ft	100ft
Slim	SLM50 (50 CFM)	Single Speed	3"	40 CFM	30 CFM	30 CFM	30 CFM
	SLM70 (70 CFM)	Single Speed	3"	50 CFM	40 CFM	30 CFM	30 CFM
	SLM70H (70 CFM)	Fan with Humidity Sensor	3"	50 CFM	40 CFM	30 CFM	30 CFM
	SLM70D (70 CFM)	Fan with Dual Speed	3"	50 CFM	40 CFM	30 CFM	30 CFM
	SLM80 (80 CFM)	Single Speed	4 inches Oval	70 CFM	60 CFM	60 CFM	60 CFM
	SLM100 (100 CFM)	Single Speed	4 inches Oval	90 CFM	80 CFM	70 CFM	70 CFM
	SLM80-110 (80-100 CFM)	Single Speed	4 inches Oval	110 CFM	100 CFM	100 CFM	90 CFM
	SLM80-110D (80-100 CFM)	Fan with Dual Speed	4 inches Oval	110 CFM	100 CFM	100 CFM	90 CFM
	SLM80-110LED (80-100 CFM)	Fan/Dimmable LED Light	4 inches Oval	110 CFM	100 CFM	100 CFM	90 CFM
	SLM80-110DLED (80-100 CFM)	Fan/Dimmable LED Light w/ Dual Speed	4 inches Oval	110 CFM	100 CFM	100 CFM	90 CFM
Integrity	ITG50 (50 CFM)	Single Speed	4 inches	50 CFM	40 CFM	40 CFM	40 CFM
	ITG50LED (50 CFM)	Fan/ Dimmable LED Light	4 inches	50 CFM	40 CFM	40 CFM	40 CFM
	ITG50HLED (50 CFM)	Fan/Dimmable LED Light w/ Humidity Sensor	4 inches	50 CFM	40 CFM	40 CFM	40 CFM
	ITG70BT (70 CFM)	Fan with Bluetooth®	4 inches	60 CFM	60 CFM	50 CFM	50 CFM
	ITG80 (80 CFM)	Single Speed	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	ITG80H (80 CFM)	Fan with Humidity Sensor	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	ITG80LED (80 CFM)	Fan/ Dimmable LED Light	4 inches	70 CFM	70 CFM	60 CFM	60 CFM
	ITG100 (100 CFM)	Single Speed	4 inches	80 CFM	80 CFM	70 CFM	70 CFM
	ITG100ELED (100 CFM)	Fan/Edge-lit Dimmable LED Light	4 inches	80 CFM	80 CFM	70 CFM	70 CFM
	ITG100RLED (100 CFM)	Fan/LED Edge-Lit Dimmable, Flat Round Panel	4 inches	80 CFM	80 CFM	70 CFM	70 CFM
Radiance	RAD80 (80 CFM)	Fan with Heater	4 inches	70 CFM	60 CFM	60 CFM	50 CFM
	RAD80LED (80 CFM)	Fan/Dimmable LED Light with Heater	4 inches	70 CFM	60 CFM	60 CFM	50 CFM
	RAD110LED (110 CFM)	Fan/Dimmable LED Light with Heater	4 inches	90 CFM	80 CFM	70 CFM	70 CFM
Professional	Pro200 (200 CFM)	Single Speed	6 inches	190 CFM	180 CFM	170 CFM	170 CFM
	Pro300 (300 CFM)	Single Speed	6 inches	270 CFM	250 CFM	230 CFM	210 CFM

The Right Fan for Any Ventilation Need

This quick guideline chart will help you match the correct bath fan size for your room size and type. HVI recommends the following intermittent ventilation rates for bathrooms:

Bathroom Size	Calculation Formula	Ventilation Rate Required
Less than 100 sq ft More than 100 sq ft	1 CFM per sq ft of floor area Add the CFM requirement for each fixture	A minimum of 50 CFM Toilet 50 CFM Shower 50 CFM Bathtub 50 CFM Jetted Tub 100 CFM

Reference: www.hvi.org/publications/HowMuchVent.cfm





Delta Breez is powerful, durable, quiet and efficient

Backed by nearly 30 years of innovation and consistent quality, the DC brushless motor technology inside every Delta Breez product is why Breez ventilation fans are the new industry standard for energy efficient performance.

All Delta Breez fans are:

- + Rigorously tested to reduce noise
- + Equipped with soft start and lock protection functions
- + Engineered to run continuously for a minimum of 70,000 hours

Energy Saving Bathroom Solution


The introduction of the Breez ventilation fan ushered in a new era in green construction for bathroom ventilation. The Breez ventilation fan delivers an aesthetically pleasing ventilation solution that consumes less power with advanced functionality, operating more quietly than most AC motor products on the market.

Features and benefits that blow you away

- + Quiet – measured at the lowest noise level (less than 0.3 sones) a bath fan can be tested for HVI certification.
- + Low Energy Costs – consumes up to 85% less energy than other leading fans, with as little as 4 Watts versus 45 Watts
- + Long-lasting features -- precision engineered Delta brushless DC fan motors for superior performance and reliability. Made to outlast AC fan motors by as much as 70%, reducing the frequency of motor replacement
- + Easy Installation – Breez retrofit models can fit into most existing bath ceiling cut-outs
- + Certification – exceeds ENERGY STAR requirements by up to 367%¹. UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring

1 Based upon ENERGY STAR V4.0 Criteria for residential ventilating fans

2 Calculations based upon U.S. average retail electricity. Actual results may vary



FAQs

Who is the Delta Group?

The Delta Group is the world's largest manufacturer of brushless DC motor fans and a leading provider of switching power supplies – a \$9 billion global company with 39 manufacturing facilities, 70 R&D labs and 169 sales offices worldwide and U.S. headquarters in Fremont, CA. Our company mission is “To provide innovative, clean and energy-efficient solutions for a better tomorrow” supported by a product portfolio that features a range of energy efficiency solutions including ventilation fans, small wind energy systems, solar panels, LED lighting, EV chargers, Industrial Automation products and Display Solution products. Delta's operations are ISO-9001, ISO-14001, ISO-14064, OHSAS-18001 and TS-16949 certified. Delta brushless DC motor fans are used in applications where precision is paramount. This includes consumer electronics products such as laptops, desktops, tablets and gaming systems from leading manufacturers.

Please visit our global website www.deltaww.com for a more comprehensive look at Delta operations, products and capabilities.

Why is a brushless DC motor better than an AC motor? Does it require any special installation or wiring?

Delta's brushless DC motor exhaust fans are engineered to run 70% longer and consume 74% less power than AC motor exhaust fans, which reduces replacement costs and saves on utility bills. No mechanical brushing means quieter operation and less wear on motor components. Delta Breez fans have been tested to run continuously for a minimum of 70,000 hours.

No special wiring is needed. There is a transformer built into the fan that automatically switches the power supply from AC to DC.

Delta's DC Breez ventilation fans are installed just like any AC motor fans.

What is the “Soft Start” Function?

In the first 10 seconds the fan is powered on, the motor will softly and quickly ramp up to full speed. This is unlike an AC Motor, which simply jump-starts the fan. This quiet 'soft start' process helps reduce the wear on motor bearings to prolong fan life.

What is the “Lock Protection” Function?

This unique function allows all Delta Breez ventilation fans to automatically power off when the impeller is abnormally locked. For example: when buildup of dirt and dust accumulates in the fan, the fan will attempt to restart itself in 5-10 seconds. If the impeller is still blocked, the fan will remain off -- this helps avoid the issue of overheating or motor burnout, reducing the risk of fire.

What is the purpose of the LED indicator light underneath the fan grille?

The light shows the user that the fan is in operation. If the fan has different functions available (i.e. humidity sensing, low speed, motion sensing), the light will change color indicating what mode the fan is in. The light will blink if the impeller gets obstructed, telling the user that the fan is not operating properly.

What are CFM and sones?

CFM and sones are how bath fans are generally compared. CFM (cubic feet per minute) measures the speed of 'air flow' – the amount of air extracted per minute when the fan is running. The amount of CFM needed is generally related to the size of the area ventilated. Please see the sizing guidelines.

Sone level represents how loud the fan is to the human ear. Doubling the sone value means double the noise. The average 80 CFM bath fan runs at 0.8~2.5 sones. Delta Breez 80 CFM fans run as low as <0.3 sones. At less than 0.3 sones, the fan is virtually silent. This is the lowest noise rating of any exhaust fan on the market. For reference, 1.0 sone is about as loud as a new computer or refrigerator. *For more information, visit <https://www.hvi.org/resources/videos/>*

How do I determine which bath fan I need – features and size?

Bathroom Ventilation

The following are Home Ventilating Institute (HVI) guidelines for ventilating both large and smaller bathrooms using intermittent or continuous ventilation.

Small rooms:

For bathrooms up to 100 square feet in area, HVI recommends that an exhaust fan provide 1 CFM per square foot (approximately eight air changes per hour) to properly ventilate the bathroom.

Example:

- Bathroom is 8' x 5' (with 8' ceilings)
Multiply $8 \times 5 = 40$ ft.
- Bathroom area is 40 ft.
- At 1 CFM per square foot the minimum recommendation is a fan rated at 40 CFM

Larger rooms:

For bathrooms above 100 square feet in area, HVI recommends a ventilation rate based on the number and type of fixtures present, according to the following table:

Toilet	50 CFM
Shower	50 CFM
Bath Tub	50 CFM
Jetted Tub	100 CFM

Note: Enclosed toilet rooms must have an operable window or a fan for ventilation

Example:

The bathroom is 20' x 12'. There is a tub (without jets), a shower enclosure and an enclosed toilet.

Each fixture requires 50 CFM:

Tub	50 CFM
Shower	50 CFM
Toilet	50 CFM
Total	150 CFM

Data source: <https://www.hvi.org/resources/publications/bathroom-ventilation/>

Or you can visit <https://www.hvi.org/resources/videos/>

How does the "Humidity Sensor" function operate?

The fan runs at full speed until the user-adjustable humidity set-point is achieved, then automatically switches to the user set low speed for continuous run or off. The amber or blue color of the LED indicator light underneath the grille shows the humidity sensing mode or continuous low speed mode. Please consult the Installation & Operating Instruction manual for your particular fan model for more specific information.

How does the "Motion Sensor" function operate?

When motion is detected, the fan comes on at full speed. When the user leaves the room, the fan will continue running at full speed until user-preset delay time has passed. Then, the fan will automatically drop down to the pre-set low speed for continuous run or off. The green or

amber color of LED indicator light underneath the grille indicates continuous low speed or full speed mode. Please consult the Installation and Operating Instruction manual for your particular fan model for more specific information.

Can I keep the housing of my old fan (non Delta fan) and just replace the fan motor with Breez?

No. For proper performance, it is recommended that Delta Breez fan motors be used only with Delta Breez fan housing.

Can I use a timer with the Delta Breez fan?

Many Delta Breez models have built-in adjustable delay timers, so no external timer is needed. External timers can be used in conjunction with single-speed models only. Because Breez fans run on much lower wattage than other market ventilation fans, please contact Delta Breez customer service for a list of single-speed models and consult with a licensed electrician for compatibility.

Do you sell switches or timers?

No. Delta does not manufacture switches or timers, but these components are readily available in most major home improvement retailers or through your local contractor or supplier.

Can the Delta Breez Fan/Light be installed with insulation around it?

Yes, all Delta Breez fans are UL approved. Here is UL's testing protocol:

For Fan/lights, UL requires 8.5 inches of insulation on all sides (including top) of the product. Insulation shall be of the loose fill type and should have a thermal resistance per inch between 3.75-3.85 R (declared by the manufacturer) when conditioned to a density of 32.04 - 40.05 kg/m³. This scenario is equivalent to an approximate R value of R32. R40 is the max for Canadian installations.

For a fan only, there is no insulation limitation for fan without lighting except in Canada where the max value is R40.

Can Delta fans be controlled by a voltage switch (RPM control)?

No.

Is LED light replaceable or are replacements available?

Delta Electronics designs our own LED modules. This is a customized LED module that cannot be replaced with an off-the-shelf, screw-in LED bulb from another manufacturer. The LED modules are designed to last a minimum of 30,000 hours, so the necessity for future replacement is unlikely. Delta Electronics has a 3-year limited warranty on every Delta designed LED module. If the LED module needs replacement outside of the warranty period, a replacement LED module can be purchased through our distributor partners or from Delta Customer Sales Support.

What are the built-in control functions and how do they work?

Motion Sensing

Green and amber LED indicator lights will show continuous low speed and full speed modes. The fan will run continuously at a user-preset lower level of CFM. When motion is detected, the fan will automatically change to full speed. When the user leaves the room, the fan will remain running at full speed until user-preset delay time has passed. The delay timer has adjustable preset positions of 0, 0.5, 5, 15, 30, 45 and 60 minutes. The fan will automatically drop down to a low speed after the pre-set time has elapsed.

Humidity Sensing

Blue and amber LED indicator lights show humidity control and full speed modes. The fan will operate in full speed mode or humidity control mode through the manual on and off switch. The adjustable humidity set points are from 50% to 90%. When in humidity control mode and the humidity is above the user-adjustable set-point, the fan will run at full speed. When the humidity is below the set-point, the fan runs continuously at a user-preset lower level of CFM.

Can Delta fans be installed in a slanted ceiling?

No, installation of any Delta fan in a slanted ceiling is not recommended.

Is it OK to exhaust into the attic?

No, the American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE) recommends exhausting only to the exterior of the home.

Can Delta fans be installed in a side wall?

Yes, all Delta BreezSlim models, BreezGreenBuilder fan

only/fan with humidity sensor models, and BreezIntegrity fan only/fan with humidity sensor models are UL listed for both ceiling and wall-mount installation.

Can I install the Exhaust Fan / Light in the shower or tub enclosure?

Yes, all Delta Breez Ventilation Fans, except BreezRadiance due to the heating element, are UL listed for use over the bathtub or shower when installed in a GFCI protected branch circuit.

How long do LEDs last?

LEDs have a rated life of up to 30,000 hours. Used for 12 hours a day, a 30,000 bulb will last more than 6 years. Used 8 hours a day, it will last more than 10 years!

Are Delta Breez fans ENERGY STAR qualified?

Yes, most Delta Breez fans are ENERGY STAR qualified. The only exception is BreezRadiance series with heater element for warmth and comfort.

Are Delta Breez fans ASHRAE 62.2-2010 compliant?

Yes, all Delta Breez fans are 62.2-2010 compliant for intermittent running. Most of the Delta Breez fan models are compliant for continuous running. Please see www.deltabreez.com, Learning Center for a complete listing.

Are Delta Breez fans UL listed and HVI certified?

Yes, all Delta Breez fans are UL listed and are HVI certified.

Do Delta Breez fans meet Title 24 requirements?

Yes, all Delta Breez fans meet current Title 24 requirements.

What is the Delta Breez Ventilation Fan Warranty?

All Delta Breez Ventilation Fans have a 3-year limited warranty.

How do I reach technical support and customer service?

Technical support: (888) 979-9889
Email: BreezTechSupport@deltaww.com

Customer sales support: (877) 685-4384
Email: BreezSalesSupport@deltaww.com
Fax: (510) 226-5098

Dealer Address:



Learn more about Breez Ventilation Fans, the best bathroom solution for green construction.

www.deltabreez.com

Delta Electronics (Americas) Ltd.

46101 Fremont Blvd.
Fremont, CA 94538

Technical support: (888) 979-9889
BreezTechSupport@deltaww.com

Customer sales support: (877) 685-4384
BreezSalesSupport@deltaww.com

Fax: (510) 226-5098

